

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 1 S., R. 38 E., Willamette Meridian, Oregon

FEET

COR	
T 1 S	R 38 39 E
S 25	S 30
S 36	S 31
ORE LIC 381	
1973	

from which reference monuments set by Voelz

An iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground for a reference monument, bears S. 46° 41' 18" W., 42.57 ft. dist., with brass cap mkd. COR REF T1S R38E R39E S25 S30 S36 S31 N47-49E 42.62'.

A bent iron post, 2 1/2 ins. diam., firmly set, leaning to the north, projecting 10 ins. above the ground for a reference monument, bears N. 47° 06' 48" W., 39.76 ft. dist., with brass cap mkd. COR REF T1S R38E R39E S25 S30 S36 S31 S46 S30E 40.09'. Remove this iron post and set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground for a reference monument, with brass cap mkd. RM T1S R38E S25 39.8 FT TO COR 2003 and an arrow pointing to the cor. (Buried the iron post set by Voelz alongside the stainless steel post.)

Corner is located at the intersection of Woodell Lane, asphalt surfaced, 20 ft. wide, extending E. and W. and Sandridge Road, graveled, 20 ft. wide, extending N. and S.

Search was made for all intervening corners. None were found.

From this same point, the cor. of secs. 29, 30, 31, and 32, bears S. 89° 58' 34" W., 5307.87 ft. dist., monumented with the original basalt stone, 13 x 10 x 2 ins., (record, 14 x 12 x 3 ins.), firmly set, projecting 6 ins. above ground, with 5 notches on the E. edge and 1 notch on the S. edge, from which the remains of an original bearing tree

A partially decayed snag, 14 ins. diam., species indeterminate, bears S. 2° E., 5.3 ft. dist., with scribe marks BT visible on open blaze. (Record, black pine, S. 20° E., 4.6 ft.)

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.

V-5

UNION COUNTY SURVEYOR	
Date Received	6/12/11
Date Filed	6/23/11
By	R. ROBINSONS, DEPUTY
File No.	019-2011R

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 1 S., R. 38 E., Willamette Meridian, Oregon

FEET	<p style="text-align: center;">T 1 S R 38 E S 30   S 29 ----- S 31   S 32 2003</p> <p>from which new bearing trees</p> <p>A tamarack, 17 ins. diam., bears N. 56½° E., 7.9 ft. dist., mkd. T1S R38E S29 BT.</p> <p>A tamarack, 14 ins. diam., bears S. 46° E., 18.5 ft. dist., mkd. T1S R38E S32 BT.</p> <p>A tamarack, 17 ins. diam., bears S. 21½° W., 19.7 ft. dist., mkd. T1S R38E S31 BT.</p> <p>A tamarack, 16 ins. diam., bears N. 61¼° W., 22.5 ft. dist., mkd. T1S R38E S30 BT.</p> <p>Deposit a magnet in a white plastic case at the base of and buried the mkd. stone alongside of the stainless steel post.</p> <p>Corner is located W., 35 ft. dist. from a dirt road, 12 ft. wide, extending N. 30° E. and S. 15° W.</p> <p>The ¼ sec. cor. of secs. 29 and 32 was searched for but not found.</p> <hr/> <p>N. 0° 05' 47" W., bet. secs. 28 and 29.</p> <p>Over broken E. slope, through fir, tamarack and pine timber with moderate undergrowth.</p> <p>2653.30 Point for the ¼ sec. cor. of secs. 28 and 29, at proportionate dist., there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 38 E 1/4 S 29   S 28 2003</p> <p>from which</p>
------	---

V-5

UNION COUNTY SURVEYOR	
Date Received	<u>6/12/11</u>
Date Filed	<u>6/23/11</u>
By	<u>R. ROBINSON, Deputy</u>
File No.	<u>019-2011R</u>