

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 1 S., R. 38 E., Willamette Meridian, Oregon

FEET	
	<p>A pine, 23 ins. diam., bears N. 18½° W., 103.2 ft. dist., with healed double blazes.</p> <p>and bearing trees mkd. by Hanley</p> <p>A pistol butt pine, 13 ins. diam., bears N. 43½° E., 117.6 ft. dist., with scribe marks T1S R38E S33 visible on partially healed upper blaze and a healed lower blaze.</p> <p>A pine, 14 ins. diam., bears S. 30½° E., 82.0 ft. dist., with healed double blazes.</p> <p>N. 0° 20' 05" E., bet. secs. 32 and 33.</p> <p>Ascend over SE. slope, through scattered pine.</p>
105	Spur, slopes E., continue over broken E. slope, through fir, tamarack, and pine timber with moderate to dense undergrowth.
2653.34	Point for the ¼ sec. cor. of secs. 32 and 33, at proportionate dist., there is no remaining evidence of the original cor.
	<p>Cement an aluminum rod, 26 ins. long, ¼ in. diam., 14 ins. in the ground, the bottom 9 ins. in a drill hole, in a mound of stone, 3½ ft. base to top, with aluminum cap mkd.</p> <p style="text-align: center;">T 1 S R 38 E 1/4 S 32 S 33 2003</p> <p>from which</p> <p>A pine, 13 ins. diam., bears N. 87½° E., 95.4 ft. dist., mkd. 1/4 S33 BT.</p> <p>A double trunk pine, 16 ins. diam., bears S. 66½° W., 36.0 ft. dist., mkd. 1/4 S32 BT.</p> <p>Deposit a magnet at the bottom of the drill hole.</p> <p>Continue over broken E. slope.</p>
5130	Spur, slopes N. 88° E., desc. over NE. slope
5306.68	Point for the cor. of secs. 28, 29, 32, and 33, at proportionate dist., there is no remaining evidence of the original cor.

V-9

**UNION COUNTY
SURVEYOR**

Date Received 6/12/11

Date Filed 6/23/11

By R. ROBINSON, DEPUTY

File No. 021-2011R

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 1 S., R. 38 E., Willamette Meridian, Oregon

FEET	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 1 S</td> <td>R 38 E</td> </tr> <tr> <td>S 29</td> <td>S 28</td> </tr> <tr> <td colspan="2" style="text-align: center;">— —</td> </tr> <tr> <td>S 32</td> <td>S 33</td> </tr> <tr> <td colspan="2" style="text-align: center;">2003</td> </tr> </table> <p>from which</p> <p>A fir, 24 ins. diam., bears N. 26¼° E., 31.6 ft. dist., mkd. T1S R38E S28 BT.</p> <p>A fir, 21 ins. diam., bears S. 16¼° E., 43.7 ft. dist., mkd. T1S R38E S33 BT.</p> <p>A fir, 17 ins. diam., bears S. 35¼° W., 10.9 ft. dist., mkd. T1S R38E S32 BT.</p> <p>A fir, 23 ins. diam., bears N. 79¼° W., 21.5 ft. dist., mkd. T1S R38E S29 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Corner is located S., 40 ft. dist. from a ravine, drains N. 50° E.</p> <p>From this point, a pile of small stones, 3 ft. base, bears N. 70° 32' 38" W., 97.63 ft. dist. These stones are identified as having the appearance of a man made mound on a survey plat by Thomas M. Hoshall, Registered Professional Land Surveyor No. 2727, in 2001, recorded in the Union County survey records, survey file No. 006-2002. This position is not utilized in this survey.</p> <p>From this same point, the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., bears N. 89° 31' 07" E., 21,122.79 ft. dist., restored but not recorded by James G. Voelz, Registered Professional Land Surveyor No. 381, in 1973, and is accepted as the best available evidence of the cor. position, monumented with a brass cap, firmly set, 3 ins. below the asphalt surface of Woodell Lane, mkd.</p>	T 1 S	R 38 E	S 29	S 28	— —		S 32	S 33	2003	
T 1 S	R 38 E										
S 29	S 28										
— —											
S 32	S 33										
2003											

V-9

UNION COUNTY SURVEYOR	
Date Received	6/12/11
Date Filed	6/23/11
By	R. ROBINSON, Deputy
File No.	021-2011R