


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner originally established by David P. Thompson in 1863 under contract No. 103. Record states: Set post for 1/4 Sec. corner in mound of stone. In 2003 a dependant resurvey was made the BLM under special instructions dated April 29, 2003. **BLM notes state: Point of 1/4 sec. cor. of secs. 32 and 33, at proportionate dist., there is no remaining evidence of the original cor. Cement an aluminum rod 26 ins. long 3/4 ins. diam., 14 ins. in the ground, in a mound of stone, 3 1/2 ft. base, to top, with aluminum cap mkd. From which a pine 13 ins. diam., bears N87 1/4°E., 94.4 ft. dist., mkd. 1/4 S33 BT. A double trunk pine, 16 ins. diam., bears S66 1/2°W., 36.0 ft. dist., mkd. 1/4 S32 BT. Deposited a magnet at the bottom.



Description of corner evidence found:

Found 3/4" aluminum rod with 3 1/4" aluminum cap set flush with ground in a 3 1/2 ft. dia. mound of stone. Cap marked as shown in diagram. A 16" dia. double trunk ponderosa pine with scribes visible on open single blaze bears S66 1/2°W - 36.0 ft. 54-9 and BLM BT signs attached. A 12" dia. ponderosa pine with scribes visible on open single blaze bears N87 1/4°E - 94.4 ft. 54-9 and BLM BT signs attached.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

William R. Wells

OREGON
JULY 22, 1977
WILLIAM R. WELLS
1106

renews 6-30-06

Description of monument and accessories I established to perpetuate the original location of this corner:

I add two new accessories.

A "XBO" chiseled on top of a 6"x8" spur of rock outcrop bears N38 1/4°W - 8.7 ft. Painted "XBO" red.

A 12" ponderosa pine scribed 1/4 S33 BT on double blaze bears S72 3/4°E - 109.9 ft. Nailed 3/4" dia. brass washer stamped "PLS 1106" to face of blaze. Attached signs 54-3 and 54-9 to tree. Painted blaze and a 6" red band around tree.

Painted blaze and 6" red band around existing bearing trees.

Set steel fence post with signs 54-2 and 54-9 5 ft. south of corner.

This corner was maintained on Oct 10, 2004. Used magnetic compass with 18° East declination and measured to accessories with a steel tape. Measurements to bearing trees are to the center of tree.

Witnesses: Jason M. Wells LSIT.

**The 2003 record by BLM is not yet recorded. We used preliminary copies of the field notes provided by the Wallowa Whitman National Forest.

Office of.....County of.....
State of, I hereby certify that the within instrument was filed
in this office for record on theday of, 20.....
.....by.....
(COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY
SURVEYOR

Date Received 12/9/04

Date Filed 12/10/04

By R. ROBINSON, DEPUTY

File No. 085-2004R

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 1 S., R. 38 E., Willamette Meridian, Oregon

FEET	
	<p>A pine, 23 ins. diam., bears N. 18½° W., 103.2 ft. dist., with healed double blazes.</p> <p>and bearing trees mkd. by Hanley</p> <p>A pistol butt pine, 13 ins. diam., bears N. 43¾° E., 117.6 ft. dist., with scribe marks T1S R38E S33 visible on partially healed upper blaze and a healed lower blaze.</p> <p>A pine, 14 ins. diam., bears S. 30¾° E., 82.0 ft. dist., with healed double blazes.</p> <p>N. 0° 20' 05" E., bet. secs. 32 and 33</p> <p>Ascend over SE. slope, through scattered pine</p>
105	<p>Spur, slopes E., continue over broken E. slope, through fir, tamarack, and pine timber with moderate to dense undergrowth.</p>
2653.34	<p>Point for the ¼ sec. cor. of secs. 32 and 33, at proportionate dist., there is no remaining evidence of the original cor.</p> <p>Cement an aluminum rod, 26 ins. long, ¾ in. diam., 14 ins. in the ground, the bottom 9 ins. in a drill hole, *in a mound of stone, 3½ ft. base, to top, with aluminum cap mkd.</p> <p style="text-align: center;">T 1 S R 38 E 1/4 S 32 S 33 2003</p> <p>from which</p> <p>A pine, 13 ins. diam., bears N. 87¾° E., 94.4 ft. dist., mkd. 1/4 S33 BT.</p> <p>A double trunk pine, 16 ins. diam., bears S. 66½° W., 36.0 ft. dist., mkd. 1/4 S32 BT.</p> <p>Deposit a magnet at the bottom of the drill hole.</p> <p>Continue over broken E. slope.</p>
5130	<p>Spur, slopes N. 80° E., desc. over NE. slope.</p>
5306.68	<p>Point for the cor. of secs. 28, 29, 32, and 33, at proportionate dist., there is no remaining evidence of the original cor.</p>

X-9

**UNION COUNTY
SURVEYOR**

Date Received 6/12/11

Date Filed 6/23/11

By R. ROBINSON, DEPUTY

File No. 022-2011 R