


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

HISTORY OF ORIGINAL CORNER ESTABLISHED:

Corner originally established by Union County Surveyor J. W. Kimbrell as part of Old Book Survey Page 192 filed October 19, 1889.

T 1 N R 39 E Z-12



Union County Survey records state:
Set stone 4 x 12 x 36 for 1/8 corner

DESCRIPTION OF CORNER EVIDENCE FOUND:

Found a stone 4" x 12" x 36" marked 1/8 on surface firmly set 20" in the ground.

SEE SURVEY NUMBER 011-2018

DESCRIPTION OF MONUMENT AND ACCESSORIES I

ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

At the position of found stone, I set a 2 1/2" x 30" aluminum pipe with a 3" aluminum cap marked as shown, 27" in the ground with mound of stone 1.5' base to top of cap,
From which:

NEW BEARING OBJECTS:

- A 5/8" x 30" iron pin bears North 9°06' East, a distance of 24.96 feet, with 1 1/2" aluminum cap marked N RP.
- A 5/8" x 30" iron pin bears South 82°59' East, a distance of 29.25 feet, with 1 1/2" aluminum cap marked E RP.
- A 5/8" x 30" iron pin bears South 13°09' East, a distance of 25.03 feet, with 1 1/2" aluminum cap marked S RP.
- A 5/8" x 30" iron pin bears North 80°59' West, a distance of 20.72 feet, with 1 1/2" aluminum cap marked W RP.

I bury the stone along the East side of the monument.
I hereby certify that the corner was perpetuated on April 6, 2018.

Witness: Kyle A. Tucker

REGISTERED
PROFESSIONAL
LAND SURVEYOR



OREGON
June 2, 2010
JEFFREY S. HSU
83571

Renewal Date: June 30, 2019

BAGETT - GRIFFITH & BLACKMAN

T1N R39E

S33

E 1/16 ——— S4

T1S

2018

OPLS 83571

UNION COUNTY
SURVEYOR

Date Received 4/25/18

Date Filed 4/25/18

Filed By [Signature]

File Number 013-201812

I used an RTK GPS in the establishment of the new accessories. Basis of Bearing is as per Survey 011-2018. The distances are to the center of the aluminum caps.