


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

HISTORY OF ORIGINAL CORNER ESTABLISHED:

None

T 1 S R 39 E Q-21



DESCRIPTION OF CORNER EVIDENCE FOUND:

None

SEE SURVEY NUMBER 019-2023

DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED TO MONUMENT THE ORIGINAL LOCATION OF THIS CORNER:

At position determined by survey I set a 5/8" x 30" iron pin, 27" in the ground, with a 2 1/2" aluminum cap, from which:


NEW BEARING OBJECTS:

A 6" Western Larch bears South 39° East, a dist. of 31.30 feet, marked S 1/16 S24 BT.
A 16" Douglas Fir bears South 74° West, a dist. of 5.10 feet, marked S 1/16 S23 BT.

Set steel fence post 1 foot North of monument.

I hereby certify that the corner was monumented on August 16th 2023.

Witness: Adam Gordon



Renewal Date: June 30, 2025

I used a steel tape and magnetic compass in the establishment of the new accessories. I used a magnetic declination of 14° East. Distances are to a 60d spike driven into the right side base of tree. Bearings are to a brass washer marked OPLS 83571 in the BT blaze of the new bearing tree.

