CERTIFIED RECORD OF LAND CORNER MONUMENTATION


HISTORY OF ORIGINAL CORNER ESTABLISHED:

Corner originally established by David P. Thompson under GLO Contract Number 103, dated July 3rd, 1863. Surveyor General Field Notes state:

Set post for corner to sec 22,23,26 and 27 in mound of earth with charred stake, pits, trench, as per instructions

In Survey Number 10, Voelz found the section corner. In Survey Number 92-73, Douglas M. Ferguson found "section corner of record, found stake in old mound of stone"

In Survey Number 74-76, Jim Voelz found stone mound and old blazed trees



DESCRIPTION OF CORNER EVIDENCE FOUND:

Found collar of embedded stone, 3 feet in diameter.

SEE SURVEY NUMBER 019-2023

DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED TO MONUMENT THE ORIGINAL LOCATION OF THIS CORNER:


At center of found mound of stone I set a 2 1/2" x 30" aluminum pipe, 26" in the ground, with a 3" $\,$ aluminum cap marked as shown below and in a 3 ft. diam. collar of stone, from which:

NEW BEARING OBJECTS:

An 8" Ponderosa Pine bears North 49° East, a dist. of 55.40 feet, marked T1S R39E S23 BT A 3" Ponderosa Pine bears South 27° East, a dist. of 30.95 feet, marked X BT A 9" Ponderosa Pine bears South 49° West, a dist. of 19.20 feet, marked T1S R39E S27 BT A 7" Ponderosa Pine bears North 66° West, a dist. of 28.65 feet, marked T1S R39E S22 BT

I hereby certify that the corner was monumented on August 1st, 2023.

Witness: Kyle Tucker, Adam Gordon



PROFESSIONAL EYOR LAND SUR\

REGISTERED

JEFFREY S. HSU 83571

Renewal Date: June 30, 2025

I used a tape and compass in the establishment of the new accessories. Bearing is measured to a brass washer labeled OPLS 83571 located at the center of BT blaze, with a declination of 14° East. Distance is measured to a 60d spike nailed to the right side base of tree.

UNION COUNTY SURVEYOR