

R623

Form 9600-9
(December 1979)
(formerly 9100-6)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

67

FIELD NOTES

OF THE

REMONUMENTATION OF CERTAIN ORIGINAL CORNER POINTS,

TOWNSHIP 1 SOUTH, RANGE 39 EAST,

UNION COUNTY
SURVEYOR

Date Received 2-2-84

Date Filed 2-21-84

By G. LANGLITZ, DEPUTY

File No. 803-84R

SHEET 1/3

Of the WILLAMETTE Meridian,

In the State of OREGON

EXECUTED BY

Scott R. McIntyre, Cadastral Surveyor

Under special instructions dated July 13, 1979, approved July 17, 1979

_____, which provided for the surveys included under U.S. Survey/Group
Number 1000, and assignment instructions dated July 30, 1982.

Survey commenced September 15, 1982

Survey completed September 17, 1982

Remonumentation of Certain Original Corner Points,
T. 1 S., R. 39 E., Willamette Meridian, Oregon

CHAINS

Set a steel fence post alongside aluminum post.

East Boundary, T. 1 S., R. 39 E.,
Willamette Meridian, Oregon

(Remonumenting a corner established by Timothy W.
Davenport, U.S. Deputy Surveyor, in 1863)

The cor. of secs. 19, 24, 25, and 30, on the E. bdy. of
the Tp., determined at record distance from the remains
of the original bearing trees:

A decayed and sawed pine stump, 8 ins. diam., bears
N. 60° E., 110 lks. dist., with axe marks visible.

A decayed and sawed pine stump, 14 ins. diam., bears
S. 75° E., 87 lks. dist., with scribe marks BT
visible on open blaze. (Record, S. 80° E.)

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 20
ins. in the ground, to solid rock, in a mound of stone,
3 ft. base, to top, with aluminum cap mkd.

T 1 S
R 39 E | R 40 E
S 24 | S 19
S 25 | S 30
1982

from which new bearing trees

A fir, 12 ins. diam., bears N. 70° E., 43 lks.
dist., mkd. T1S R40E S19 BT.

A fir, 12 ins. diam., bears S. 28° E., 37 lks.
dist., mkd. T1S R40E S30 BT.

A fir, 14 ins. diam., bears S. 11° W., 35 lks.
dist., mkd. T1S R39E S25 BT.

A fir, 13 ins. diam., bears N. 67° W., 31½ lks.
dist., mkd. T1S R39E S24 BT.

Set a steel fence post alongside aluminum post.

Subdivisions, T. 1 S., R. 39 E.,
Willamette Meridian, Oregon

(Remonumenting a corner established by David P. Thompson,
U. S. Deputy Surveyor, in 1863, and
perpetuated by John W. Kimbrell,
U. S. Deputy Surveyor, in 1888)

The cor. of secs. 23, 24, 25, and 26, determined from the
remains of bearing trees mkd. by Kimbrell:

A root hole, bears S. 88° E., 33 lks. dist.
(Record, N. 88° E.)

UNION COUNTY
SURVEYOR

Date Received 2-2-84

Date Filed 2-21-84

By G. LANGUITZ, DEPUTY

File No. 802-84 R

SHEET 2/3

Remonumentation of Certain Original Corner Points.
T. 1 S., R. 39 E., Willamette Meridian, Oregon

CHAINS

A fir snag, 17 ins. diam., bears S. 27° E., 34 lks. dist., with illegible scribe marks visible on open and decayed blaze. (Record, S. 31° E.)

A root hole, bears S. 33° W., 8 lks. dist. (Record, S. 30° W.)

A fir snag, 25 ins. diam., bears N. 27° W., 12 lks. dist., no marks visible on open and decayed blaze. (Record, N. 31° W.)

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, to solid rock, in a mound of stone, 3½ ft. base, to top, with aluminum cap mkd.

T 1 S R 39 E
S 23 | S 24
S 26 | S 25
1982

from which new bearing trees

A fir, 15 ins. diam., bears N. 72° E., 96 lks. dist., mkd. T1S R39E S24 BT.

A fir, 28 ins. diam., bears S. 61° E., 38 lks. dist., mkd. T1S R39E S25 BT.

A fir, 14 ins. diam., bears S. 24° W., 26 lks. dist., mkd. T1S R39E S26 BT.

A fir, 22 ins. diam., bears N. 68° W., 33 lks. dist., mkd. T1S R39E S23 BT.

Set a steel fence post alongside aluminum post.

UNION COUNTY
SURVEYOR

Date Received 2-2-84

Date Filed 2-21-84

By G. LANGLITZ, DEPUTY

File No. 802-84R

SHEET 3/3