

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

A-17


History of original corner establishment:

Corner established in 1882 by Henry Meldrum, Deputy Surveyor under Contract No. 450.

Surveyor General's records states:

Set a basalt stone 16 x 10 x 5", 11" in the ground for closing corner to secs. 2 and 3, jkd. CC on S, with 2 notches on E and 4 notches on W edge; and raised a mound of stone alongside. Pits impracticable.

No trees in limits.



Description of corner evidence found:

At assumed corner location I found 16 x 9 x 6" basalt stone 9" above ground. Found no markings on stone, however the stone was upright in a mound and we confirmed the location both along the base line and from the 1/4 corner to the South.

Description of monument and accessories I established to perpetuate the original location of this corner

I set a 2" galv. iron pipe with brass cap approx. 8" above the surface of the ground in a mound of stone 3 ft. dia. and 1 ft. high. Cap stamped as shown above.

Bearing tree:

A 10" P. pine bears S 57 E, 113.30 ft. scribed T 1 S R 40 E S 2 CC BT.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

James H. Hambleton

OREGON
JULY 10, 1964
JAMES H. HAMBLETON
645

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office
for record on the day of
..... by
(COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY SURVEYOR	
Date Received	_____
Date Filed	_____
By	_____
File No.	<u>121-84R</u>