


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

A-20

History of original corner establishment:

No previous history.



THIS CORNER IS LOCATED ALONG THE NORTH LINE OF SEC. 2 AND REFERS TO SEC. 2 ONLY. CONFIRMED VIA TELEPHONE WITH J. HAMBLETON. 5-28-81 J. Langley, DEPUTY CO. SURVEYOR

Description of corner evidence found:

None

Description of monument and accessories I established to perpetuate the original location of this corner

I set a 1" galv. iron pipe with brass cap approx. 18" above surface of ground in a mound of stone 3 ft. dia. and 1 1/2 ft. high. Cap stamped as shown above.

Bearing trees:

A9" P. pine bears S 65 W, 3.0 ft. scribed 1/16 S BT.

A 7" P. pine bears S 85 E, 47.10 ft. scribed 1/16 S BT.

REGISTERED PROFESSIONAL LAND SURVEYOR

James H. Hambleton

OREGON
JULY 18, 1984
JAMES H. HAMBLETON
645

Office of..... County of.....
 State of....., I hereby certify that the within instrument was filed in this office
 for record on the day of ..
 by
 (COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY SURVEYOR

Date Received _____

Date Filed _____

By _____

File No. 123-84 R

☆ GPO 796-333