

UNION COUNTY SURVEYOR

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

HISTORY OF ORIGINAL CORNER ESTABLISHMENT:


None

DESCRIPTION OF CORNER EVIDENCE FOUND:

NONE

See Union County Survey 033-1998

T 1 S R 40 E B-11



DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

At position determined by survey, I set a 2½" x 30" aluminum pipe with aluminum cap marked as shown below, 27" in the ground from which:

A 15 inch Douglas Fir bears N27°E, a distance of 56.60 feet, marked CN 1/16 BT.

A 15 inch Douglas Fir bears N34°W, a distance of 38.40 feet, marked CN 1/16 BT.

I hereby certify that the corner was monumented on August 28, 1998.
Witness: Jeff Madsen, Norbert Volny, Greg Blackman Jr.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Nick G. Robinson

OREGON
July 17, 1986
RICK G. ROBINSON
2219

Renewal Date December 31, 1998

BAGETT - GRIFFITH & BLACKMAN

T1S R40E

C

N 1/16 S 4

C

1998

OPLS 2219

UNION COUNTY SURVEYOR

Date Received 9/2/98

Date Filed 9/26/98

Filed By *Gregory T. Blackman*

File Number 068-1998R

I used a steel tape and magnetic compass in the establishment of the new accessories. I used 18° East declination, the distances are to a 60d spike driven into the root crown of the bearing tree. A brass washer marked OPLS 2219 is attached to the BT blaze.

B-11