

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

C-21

History of original corner establishment:


Corner established by Henry Meldrum, Deputy Surveyor in 1882, under Contract No. 450.

Surveyor General's records states:

Set basalt stone, 18 x 12 x 8", 12" in the ground for $\frac{1}{4}$ sec. cor. mkd. $\frac{1}{4}$ on W face; from which

A 15" pine bears S 58 E, 36 lks. mkd. $\frac{1}{4}$ S BT.

A 18" pine bears S 58 W, 95 lks. mkd. $\frac{1}{4}$ S BT.



Description of corner evidence found:

At assumed corner location I found an 18 x 12 x 8" basalt stone 8" above ground in good condition with $\frac{1}{4}$ mkd. on W face.

Found a 20" P. pine bears S 58 W, 95 lks. with face partially opened.

Found a live and in good condition a 28" P. pine bears S 58 E, 36 lks. with face partially opened and $\frac{1}{4}$ S scribing visible.

Description of monument and accessories I established to perpetuate the original location of this corner

I set a 2" galv. iron pipe with brass cap approx 2" above surface of ground in a mound of stone 3 ft. dia. and 1 ft. high with original stone upside down along the west edge of pipe. Cap stamped as shown above.

Bearing trees:

A 6" E. fir bears S 47 30 W, 23.15 ft. scribed $\frac{1}{4}$ S BT.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

James H. Hambleton

OREGON
JULY 10, 1964
JAMES H. HAMBLETON
645

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office
for record on the day of ..
..... by ..
(COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY SURVEYOR	
Date Received	_____
Date Filed	_____
By	_____
File No.	130-84 R