


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. C-25

History of original corner establishment:

Original corner established in 1882 by H. Meldrum under contract #450. He set a post, 3'x3"x3", 24" in ground. From which: A 12" Fir bears N71°E, 16 lks. A 14" Fir bears N81°W, 18 lks.



Note: A Gesener resurveyed this line in 1898 under contract #683. At that time, the NE BT had fallen down, so he marked: An 8" Fir bearing S76°E, 50 lks.

Description of corner evidence found:

No corner monument found.

Bearing trees found:

25 1/2" Fir bears S76°E, 33.1 ft., blaze healed, original BT. 27 1/2" Fir bears N79°W (Orig. bearing N81°W), 11.9 ft.

Description of monument and accessories established to perpetuate the original location of this corner:

Cap is stamped:

T1S T1S R41E SC 1/2 S1 R40E RLS 1848 1986

From evidence, set 2 1/2"x30" aluminum capped aluminum pipe rising 5" above ground. Set steel fence post 3.1 ft. north of corner.

New BT:

A 7 1/2" Fir bears S9 1/2°W, 27.4 ft., blazed & scribed 1/2 S1 SCBT

Painted blazes and attached signs as required in Specifications for Cadastral Surveys, USFS Region 6, March, 1982. A 3/4" brass disk stamped "LS1848 nailed to lower end of blazes. To find corner go to the end of rd. 6200-600. Follow posted line north 0.4 miles to the corner.

Compass Declination: 19 1/2°E Witness: Jeremy Sutton



UNION COUNTY SURVEYOR Date Received 11-21-86 Date Filed 11-26-86 By G. LANGLITZ, DEPUTY File No. 263-86 R

I hereby certify that the above described corner monument and/or accessories was perpetuated as hereon described on July 09, 1986.

Office of..... County of..... State of..... I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19..... by..... (COUNTY OFFICIAL) (DEPUTY)