

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

HISTORY OF ORIGINAL CORNER ESTABLISHED:


Corner originally established by Henry Meldrum under GLO contract 450, dated June 11, 1882. Surveyor General field notes state:

Set basalt stone 18x9x5 ins., 12 ins in ground for cor. to secs 5, 6, 7 and 8, marked with 5 notches on S and 5 notches on E edges and raised mound of stone slongside. From which:

A pine 50 ins. in dia. bears N37°W, 191 lks. dist. marked T1S R40E S6 BT.

Bearing tree recovered by James Voelz in Survey Number 53-74. Position used for section corner, but no indication of a stone found or monument set.

T 1 S R 40 E E-05



DESCRIPTION OF CORNER EVIDENCE FOUND:

Monument not found. Established a position by retracement of Survey 53-74. From position as established, a 50" stump bears North 40° West, a distance of 127 feet. No scribe marks found. Corner falls 13 feet South of a rock jack from which fences bears East and South.

SEE PARTITION PLAT NUMBER 20160020T

DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED

TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

At the position determined by survey, I set a 2 1/2" x 30" aluminum pipe monument, with 2 1/2" aluminum cap attached, marked as shown below, 15" in the ground, in a collar of stone, 2 ft. in diameter, from which:

NEW BEARING OBJECTS:

- A 12" Ponderosa Pine bears North 21° East, a distance of 38.70 feet, marked T1S R40E S5 BT.
- A 13" Ponderosa Pine bears South 88° East, a distance of 41.80 feet, marked T1S R40E S8 BT.
- A 27" Ponderosa Pine bears South 13° West, a distance of 41.20 feet, marked T1S R40E S7 BT.
- A 19" Ponderosa Pine bears North 65° West, a distance of 25.55 feet, marked T1S R40E S6 BT.

I hereby certify that this monument was set October 11, 2016.

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**



OREGON
June 2, 2010
JEFFREY S. HSU
83571

Renewal Date: June 30, 2017

BAGETT - GRIFFITH & BLACKMAN

T1S R40E

S6	S5
S7	S8

2016

OPLS 83571

**UNION COUNTY
SURVEYOR**

Date Received 10/31/16

Date Filed 10/31/16

Filed By [Signature]

File Number 040-201602

I use a steel tape and magnetic compass in the establishment of the bearing trees. Magnetic declination used was 15° East. Distances are to a spike in the root crown of the trees. Bearings are to a brass washer in the lower blaze marked OPLS 83571.