UNION COUNTY SURVEYOR

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

HISTORY OF ORIGINAL CORNER ESTABLISHMENT:

Corner originally established by Henry Meldrum under GLO contract Number 450, dated December 1, 1882. Surveyor General record states:

Set basalt stone 24x18x12, 18" in ground marked 1/4on North face from which:

A Ponderosa Pine 48" dia. bears N41°E, 98 lks. A Ponderosa Pine 40" dia. bears S53°E, 42 lks.

No record of subsequent monumentation found in Union County survey records.

DESCRIPTION OF CORNER EVIDENCE FOUND:

Found basalt stone 24x18x12 marked 1/4 on North face. Found 32" badly decayed stump at record bearing and distance from stone for the NE bearing tree. Found no evidence of the SE bearing tree.

See Union County Survey 033-1998

DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

In place of the found marked stone, I set a 2½"x30" aluminum pipe with aluminum cap marked as shown, 14 inches in the ground with mound of stone 2feet at the base with found stone buried to the South, from which:

A 12" Ponderosa Pine bears N24°E, a distance of 80.27 feet, marked 1/4 S4 BT. A 19" Ponderosa Pine bears S69°W, a distance of 59.07 feet, marked 1/4 S9 BT. A 13" Douglas Fir bears S70°W, a distance of 68.47 feet, marked 1/4 S9 BT.

A 13" Ponderosa Pine bears N5°W, a distance of 83.59 feet, marked 1/4 S4 BT.

I hereby certify that the corner was monumented on August 21, 1998. Witness: Norbert Volny, Jeff Madsen, Greg Engelgau


REGISTERED **PROFESSIONAL** LAND SURVEYOR

> **OREGON** July 17, 1986

RICK G. ROBINSON

2219

Renewal Date December 31, 1998



T1S R40E E-11

4

UNION COUNTY **SURVEYOR**

I used a steel tape and magnetic compass in the establishment of the new accessories. I used 18° East declination, the distances are to a 60d spike driven into the right side of the root crown of the bearing trees. A brass washer marked OPLS 2219 is attached to the BT blaze.