

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


E-13

History of original corner establishment:

Corner established in 1882 by Henry Meldrum, Deputy Surveyor under Contract No. 450.

Surveyor General's records states:

Set a basalt stone 20 x 10 x 7", 15" in the ground for cor. to secs. 3, 4, 9 & 10, mkd. with 5 notches on S and 3 notches on E edge; and raised mound of stone alongside. Pits impracticable. from which:



A 36" pine bears N 34 W, 78 lks. mkd. T 1 S S 4 BT.

A 15" pine bears S 1 W, 191 lks., mkd. S 9 BT.

A 10" pine bears N 51 E, 140 lks. mkd. R 40 E S 3 BT.

Description of corner evidence found:

At assumed corner location I found 20 x 10 x 7" basalt stone 10" above ground in good condition with 5 notches on S and 3 notches on E.

Found approx. 36" charred pine stump bears N 34 W, 78 lks.

Found approx. 30" pine stump bears N 51 E, 140 lks. with BT scribed on blaze face.

Found approx. 22" pine snag bears S 01 W, 191 lks. with blaze partially grown over; scribing visible.

Found raised mound of stone along side cor. stone.

Description of monument and accessories established to perpetuate the original location of this corner

I set a 2" galv. iron pipe with brass cap approx. 6" above surface of ground in a mound of stone 3 ft. dia. and 1 ft. high; buried original stone upside down along west side of pipe. Cap stamped as shown above.

New bearing trees:

A 9" P. pine bears N 30 E, 99.75 ft. and scribed T 1 S R 40 E S 3 BT.

A 6" D. fir bears N 34 W, 104.25 ft. scribed T 1 S R 40 E S 4 BT.

A 14" P. pine bears S 44 W, 68.25 ft. scribed T 1 S R 40 E S 9 BT.

A 11" P. pine bears S 05 E, 63.83 ft. scribed T 1 S R 40 E S 10 BT.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

James H. Hambleton

OREGON
JULY 10, 1954
JAMES H. HAMBLETON
645

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office
for record on the day of.....
..... by.....
(COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY SURVEYOR	
Date Received	_____
Date Filed	_____
By	_____
File No.	<u>134-84R</u>