

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

E-23

History of original corner establishment:


Corner was established in 1882 by Henry Meldrum, Deputy Surveyor under Contract No. 450.

Surveyor General's records state:

Set post, 3 ft. long, 3" sq., 24" in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ S on N. face; from which

A pine, 30" dia., bears N 29 W, 108 lks. dist., mkd. $\frac{1}{4}$ S BT.

A pine, 48" dia., bears S 27 W., 6 lks. dist., mkd. $\frac{1}{4}$ S BT.



Description of corner evidence found:

At assumed corner location I found no evidence of the post.

I found a 36 in. pine stump partly rotted with face and portion of BT scribed on face which bears S 27 W, 6 lks. from assumed corner position.

Found a 36" dia. pine stump hole with portions of rotted wood which bears N 29 W, 108 lks. from assumed corner.

Description of monument and accessories I established to perpetuate the original location of this corner

I set a 2" galv. iron pipe 30" long with brass cap, 6" above ground in a mound of stone stamped as shown above.

I set two new bearing trees:

A 9" pine which bears N 28 30 E, 14.54 feet and scribed $\frac{1}{4}$ S BT.

A 8" red fir which bears S 47 30 E, 52.54 ft. scribed $\frac{1}{4}$ S BT.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 10, 1894
JAMES H. HAMBLETON
645

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office
for record on the day of.....
..... by
(COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY SURVEYOR	
Date Received	_____
Date Filed	_____
By	_____
File No.	145-84R