CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1882 by Henry Meldrum, Deputy Surveyor under Contract No. 450.

Surveyor General's records states:

Set a basalt stone, $16 \times 8 \times 6$ ", 11" in the ground for cor. to secs. 10, 11, 14 and 15, mkd. with 4 notches on S and 2 on E

edge, 350 ft. above last brook; from which


A 36" pine bears N 62 W, 37 lks. mkd. T 1 S S 10 Bt.

A 30" pine bears S 30 W, 37 lks. mkd. R 40 E S 15 BT.

A 30" pine bears S 57 E, 49 lks. mkd. S 14 BT.

A 40" pine bears N 31 E, 121 lks. mkd. S 11 BT.

Description of corner evidence found:



SHOULD BE T.15.

BY G. LANGLITZ, DEPUTY Co. SURVEYOR 5-31-84

At assumed corner location I found 16 x 8 x 6" basalt stone with 4 notches on S and 2 notches on E. Found 30" pine snag bears S 57 E, 49 lks. and with scribing 14 S visible on blazed face.

Found 30" pine snag uprooted bears S 30 W, 37 lks. no visible scribing.

Found no other evidence acceptable.

Description of monument and accessories I established to perpetuate the original location of this corner

I set a 2" galv. iron pipe with brass cap approx. 8" above surface of ground in a mound of stone approx. 3 ft. dia. and 1 ft. high; placed original stone along the west side of the monument. Cap stamped as shown above.

Bearing trees:

A 9" D. fir bears N 28 W, 59.83 ft. scribed T 1 S R 40 E S 10 BT.

A 10" D. fir bears N 38 E, 26.92 ft. scribed T 1 S R 40 E S 11 BT.

A 9" P. pine bears S 83 00 E, 47.83 ft. scribed T 1 S R 40 E S 14 BT.

A 10 P. pine bears S 73 W, 18.75 ft. scribed T 1 S R 40 E S 15 BT.

REGISTERED **PROFESSIONAL** LAND SURVEYOR

OREGON

		645
Office of		13/2/2/2
for record on the day of	instrument was filed	
(COUNTY OFFICIAL)	#*************************************	
(SOUNT DEFICIAL)	(DEPUTY)	UNION COUNTY

Form R6-7100-57 (9/71)

Date Received

Cate Filed

± GPO 796-333