

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

J-19

History of original corner establishment:


Corner established in 1882 by Henry Meldrum, Deputy Surveyor under Contract No. 450.

Surveyor General's records states:

Set a post, 3 ft. long, 3" sq. 24" in the ground, for $\frac{1}{4}$ sec. cor. mkd $\frac{1}{4}$ S on N face from which:

A 15" tamarack bears N 34° W, 23 lks. mkd. $\frac{1}{4}$ S BT.

A 8" Tamarack bears S 33° W, 17 lks. mkd. $\frac{1}{4}$ S BT.



Description of corner evidence found:

At assumed corner location I found no trace of wooden post. Due to extensive logging activity in the immediate area of this $\frac{1}{4}$ cor. all evidence of the original corner has been destroyed.

Description of monument and accessories I established to perpetuate the original location of this corner

I set a 2" galv. iron pipe with brass cap in a mound of stone and soil 3 ft. dia. and 1 ft. high. Monument is 3" above surface; too rocky to bury any deeper. Cap stamped as shown above. Corner set by proportionate measurements.

Bearing trees:

A 8" larch bears N $10^{\circ} 30'$ E, 66.6 ft. scribed $\frac{1}{4}$ S BT.

A 6" larch bears S $23^{\circ} 30'$ W, 34.04 ft. scribed $\frac{1}{4}$ S BT.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

James H. Hambleton

OREGON
JULY 10, 1964
JAMES H. HAMBLETON
645

Office of..... County of.....
State of....., I hereby certify that the within Instrument was filed in this office
for record on the day of

..... by
(COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY
SURVEYOR

Date Received _____

Date Filed _____

By _____

File No. 169-84 R