


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

J-23



History of original corner establishment:

Corner established in 1882 by Henry Meldrum, Deputy Surveyor under Contract No. 450.

Surveyor General's records state:

Set basalt stone, 16 x 8 x 6", 9" in the ground for  $\frac{1}{4}$  sec. Cor. mkd.  $\frac{1}{4}$  on N. face; from which:

A 9" tamarack bears N 58 W, 15 lks. mkd.  $\frac{1}{4}$  S BT.

A 36" pine bears S 24 W, 12 lks. mkd.  $\frac{1}{4}$  S BT.

Description of corner evidence found:

At assumed corner location found 18 x 10 x 8" basalt stone 12" above ground in good condition with  $\frac{1}{4}$  marked on the N face. Also found 20" larch stump with face grown over and partially cut open bearing N 58 W, 15 lks.

Also found badly rotted pine remains of a stump fitting the bearing tree calls in Sec. 13

Description of monument and accessories established to perpetuate the original location of this corner

I set a 2" galv. iron pipe with brass cap approx. 6" above ground surface in a mound of stone with cap stamped as shown above. Placed original stone upside down on W side of monument.

Set two new bearing trees:

A 10" larch bears N 26 W, 51.25 ft. and scribed  $\frac{1}{4}$  S BT.

A 9" larch bears S 69 E, 20.0 ft. and scribed  $\frac{1}{4}$  S BT.

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*James H. Hambleton*

OREGON  
JULY 10, 1964  
JAMES H. HAMBLETON  
645

Office of..... County of.....  
State of....., I hereby certify that the within instrument was filed in this office  
for record on the ..... day of .....

(COUNTY OFFICIAL)

by ..... (DEPUTY)

UNION COUNTY SURVEYOR	
Date Received	_____
Date Filed	_____ <small>645 706 333</small>
By	_____
File No.	171-84R