

**UNION COUNTY SURVEYOR**

**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

**HISTORY OF ORIGINAL CORNER ESTABLISHMENT:**

Corner Not previously established

**DESCRIPTION OF CORNER EVIDENCE FOUND:**


NONE

See Union County Survey 043-1998

**DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:**

At position determined by survey, I set a 2½" x 30" aluminum pipe with aluminum cap marked as shown below, 26" in the ground from which:

T 1 S R 40 E L -11



A 11 inch Tamarack bears S51°57'E, a distance of 99.14 feet, marked C1/4 S16 BT.

A 12 inch Douglas Fir bears S35°22'W, a distance of 90.83 feet, marked X BT.

A 15 inch Douglas Fir bears N88°35'W, a distance of 74.40 feet, marked C1/4 S16 BT.

A 8 inch Ponderosa Pine bears N11°09'W, a distance of 29.84 feet, marked C1/4 S16 BT.

I hereby certify that the corner was monumented on October 13, 1998.

Witness: Norbert Volny and Greg Englegau

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Rick G. Robinson*

OREGON  
July 17, 1988  
RICK G. ROBINSON  
2219

Renewal Date December 31, 1998

BAGETT - GRIFFITH & BLACKMAN

T1S R40E

C1/4

S16

1998

OPLS 2219

**UNION COUNTY  
SURVEYOR**

Date Received 10/16/98

Date Filed 10/20/98

Filed By *Avery T. Black*

File Number 085-1998R

I used a total station instrument in the establishment of the new accessories. I used the same basis of bearing as survey number 043-1998, and the distances are to a 60d spike driven into the root crown of the bearing tree. A brass washer marked OPLS 2219 is attached to the BT blaze.