

LINE TREE
M-1 TO N-1


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Line Tree between corners M-25 & N-25

History of original corner establishment:

Original line tree established in 1882 by Henry Meldrum under contract #450. At 18.84 chains, a 26" Yellow Pine, a line tree marked with 2 notches on the N. & S. sides.

In resurvey by Alonzo Gesner in 1898 under Contract No. 683, he stated he found a 24" Yellow Pine with 2 notches on N & S sides at 19.03 chains.



Description of corner evidence found:

I found a 33½" Ponderosa Pine, live, good condition with 2 notches on the north and south sides.

Description of monument and accessories I established to perpetuate the original location of this corner:

I removed the loose bark at 6 ft. high, painted a red band and nailed 54-9 signs on the north and south sides.

New BT's:

- A 9½" Doug Fir bears S57°E, 22.1 ft., blazed&scribed: APT1SR41ES18BT
- An 8½" Doug Fir bears S26°W, 16.9 ft., blazed&scribed: APT1SR40ES13BT

Painted blazes and attached signs as per Standard Specifications for Cadastral Surveys, USFS Region 6, March 1982. A ¾" brass disk stamped "RLS 1848" was nailed to the lower end of the blazes.

To find corner, from 6200489 follow 6200485 southerly and westerly ¼ mile to where it curves and goes south down hill. A private road goes NW'ly through gate, follow fence line North 350 feet to line tree 10 feet west of fence on gentle westerly slope.

Compass declination: 19½°E
Witness: Jeremy Sutton

I hereby certify that the above described corner monument and/or accessories were established as hereon described on Nov. 11, 1986.



UNION COUNTY SURVEYOR	
Date Received	12-18-86
Date Filed	12-24-86
By	G. LANGRIZ, Deputy
File No.	325-86 R

Office of..... County of.....
 State of....., I hereby certify that the within instrument was filed in this office
 for record on the..... day of....., 19.....
 by
 (COUNTY OFFICIAL) (DEPUTY)