


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. N-25

History of original corner establishment:

Original corner established in 1882 by H. Meldrum under contract #450. He set a post, 4'x4"x4", 24" in ground. From which: An 8" Fir bears N40°E, 8 lks. A 10" Fir bears N11°W, 11 lks. A 12" Pine bears S35°W, 31 lks. A 6" Fir bears S40°E, 8 lks.



Note: Alonzo Gesener stated in 1898 when he resurveyed the range line under contract No. 683 he found the corner marked and witnessed as stated by the Surveyor General.

Description of corner evidence found:

No corner monument found.

Bearing trees found:

A 2 1/2" Fir bears N11°W, 7.26 ft., Scribing visible: S13

Description of monument and accessories established to perpetuate the original location of this corner:

Cap is stamped:

From evidence, set a 2 1/2"X30" aluminum capped aluminum pipe rising 6" above ground. Set steel fence post 3 ft. north of corner.


T1S T1S
S13|
S24|R41E
R40E S18
RLS 1848
1986

New BT's:

An 8 1/2" D. Fir bears S66°W, 59.2 ft., blazed&scribed T1SR40ES24BT
A 6" W. Fir bears N77 1/2°W, 24.6 ft., blazed&scribed T1SR40ES13BT

Painted blazes and attached signs as required in Specifications for Cadastral Surveys, USFS Region 6, March, 1982. A 3/4" brass disk stamped "LS1848 nailed to lower end of blazes. To find corner take Rd. 6200-485 southerly and westerly 1/2 mi. from 6200489. Follow posted line 700 ft. south to corner.

Compass Declination: 19 1/2°E
Witness: J. Sutton
I hereby certify that the above described corner monument and/or accessories was perpetuated as hereon described on July 25, 1986.



UNION COUNTY SURVEYOR
Date Received 11-21-86
Date Filed 11-26-86
By G. LANGWITZ DEPUTY
File No. 267-86 R

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....
(COUNTY OFFICIAL) by (DEPUTY)