


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. P-25

History of original corner establishment:

Original corner established in 1882 by H. Meldrum under contract #450
He set a post, 3'x3"x3", 24" in ground.
From which:
A 10" Fir bears N35°W, 16 lks.
A 10" Fir bears S72°E, 19 lks.



Note: A. Gesener resurveyed this line in 1898 under contract #683. He mentioned that he found the corner marked and witnessed as stated by the surveyor general.

Description of corner evidence found:

No corner monument found.

Bearing trees found:

Rotted remains of original BT N35°W, 16 lks. with chop marks.
No scribing visible.
A 24½" Fir bears S72°E, 19 lks.
blaze & scribing visible: ¼ S BT

Description of monument and accessories | established to perpetuate the original location of this corner:

Cap is stamped:

From evidence, set 2½"x30" aluminum capped aluminum pipe rising 10" in mound of stones
Set steel fence post 3 ft. north of corner.

T1S T1S
¼S24 | R41E
R40E
RLS 1848
1986

New BT's:

A 8½" Spruce bears N28°W, 81.2 ft.,
blazed&scribed ¼S24BT
An 11½" W. Fir bears S58°W, 37.3 ft.,
blazed&scribed: ¼S24BT

Painted blazes and attached signs as required in Specifications for Cadastral Surveys, USFS Region 6, March, 1982. A ¾" brass disk stamped "LS1848" nailed to lower end of blazes.
To find corner take Rd. 6100-484 to where it crosses the Forest Service boundary. Follow posted line north 400 ft. to corner.

Compass Declination: 19½°E
Witness: Jeremy Sutton

I hereby certify that the above described corner monument and/or accessories was perpetuated as hereon described on Aug 29, 1986.

REGISTERED
PROFESSIONAL
LAND SURVEYOR
B. A. Sutton
OREGON
JULY 13, 1979
B. A. SUTTON
1848

**UNION COUNTY
SURVEYOR**

Date Received 11-21-86
Date Filed 11-26-86
By G. LANGLITZ, DEPUTY
File No. 268-86R

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office
for record on the..... day of....., 19.....
..... by

(COUNTY OFFICIAL)

(DEPUTY)