

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

HISTORY OF ORIGINAL CORNER ESTABLISHMENT:

None

No record of further monumentation found in Union County survey records.

DESCRIPTION OF CORNER EVIDENCE FOUND:

NONE

See Survey Number 042-2004

DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

At the position determined by the survey I set a 5/8" x 30" rebar with 2 1/2" aluminum cap 30 inches in the ground, marked as shown, from which:


NEW BEARING OBJECTS AND TREES:

A 4 inch Dia. Ponderosa pine bears N 22°E, a distance of 91.70 feet, marked W 1/16 S21°E BT

A 6 inch Dia. White fir bears S 40° E, a distance of 40.95 feet, marked W 1/16 S 28 BT

I hereby certify that the corner was monumented on December 22, 2004. Witnesses: Mike Spicer, Greg Blackman Jr.

T 1 S R 40 E R-10



REGISTERED
PROFESSIONAL
LAND SURVEYOR

Greg T. Blackman

OREGON
JULY 13, 1973

GREGORY T. BLACKMAN
991

Renewal Date: December 31, 2005

BAGETT GRIFFITH & BLACKMAN

T 1 S R 40 E

W 1/16 S 21
 S 28

2004

OPLS 991

**UNION COUNTY
SURVEYOR**

Date Received 12/30/04

Date Filed 12/30/04

Filed By R. ROBINSON, DEPUTY

File Number 107-2004R

I used a steel tape and magnetic compass in the establishment of new accessories. The Magnetic declination used was 18° East. The distance to the bearing tree is to a 50d spike driven in the right side of the tree at the root crown. I attached a brass washer marked OPLS 991 to the BT blaze.