


**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

Index File No. T-21

**History of original corner establishment:**

Corner was originally established by Henry Meldrum, Deputy Surveyor, under G.L.O. contract No. 450, during August 1882. Surveyors General's notes state: "Set post 3 ft. long, 3 ins. sq., 24 ins. in the ground for 1/4 sec. cor., mkd. 1/4 on W. face; from which a fir, 12 ins. diam. bears S50°W., 25 lks. dist. mkd., 1/4S BT. An alder, 4 ins. diam. bears N72°E., 35 lks. dist. mkd., 1/4S BT."



**Description of corner evidence found:**

Found no trace of record post or BTs.

**Description of monument and accessories established to perpetuate the original location of this corner:**

At surveyed point set 2 1/2" x 30" galvanized pipe and brass cap marked: Set pipe 25" in the ground. From which by magnetic declination of N20°E: A 14" Fir bears N68°E., 85.9 ft. scribed 1/4S25 BT. A 11" Fir bears S89°W., 20.9 ft. scribed 1/4S26 BT. Painted blazes red and 6" red band around. Placed 54-3s and brass washers stamped PLS 1051 on BTs. Placed 54-4 on a steel fence post 5' north of the corner.

TLS R40E  
1/4  
S26 + S25  
OR PLS 1051  
1981

I hereby certify that the above corner monument was reestablished as herein described.

Witnesses: Daniel Rowland  
Troy Phillips

July 29, 1981

**REGISTERED  
PROFESSIONAL  
LAND SURVEYOR**

*Barry B. Barbour*  
**OREGON  
OCT. 17, 1975  
BARRY B. BARBOUR  
1051**

Office of...County...Surveyor..... County of.....Union.....

State of...Oregon....., I hereby certify that the within instrument was filed in this office

for record on the...10th day of...August....., 1981.

*Howard L. Perry*  
(COUNTY OFFICIAL)

by *Mary J. Langitt*  
(DEPUTY)

**UNION COUNTY  
SURVEYOR**

Date Received \_\_\_\_\_  
\* GPO-758-278

Date Filed \_\_\_\_\_

By \_\_\_\_\_

File No. 181-84 R