


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

This Section Corner was set by Deputy Surveyor Henry Meldrum, under contract No. 450, dated June 11, 1882. He states he set a post 4 ft. long 4 in. sq., 24 in. in the ground, for the corner to Sections 29, 30, 31 and 32 marked T 1 S S 29 on the NE and R 40 E S 30 on the NW, S 31 on the SW and S 32 on the SE faces with one notch on the south and 5 notches on the east edges from which he set:

- A pine 12 in. dia. bears N 55 E, 69 lks. dist. marked T 1 S R 40 E S 29 BT.
- A pine 24 in. dia. bears S 21 E, 12 lks. dist. marked T 1 S R 40 E S 32 BT.
- A pine 10 in. dia. bears S 60 W, 20 lks. dist. marked T 1 S R 40 E S 31 BT.
- A pine 10 in. dia. bears N 26 W, 21 lks. dist. marked T 1 S R 40 E S 30 BT.



Description of corner evidence found:

In the vicinity of this section corner there has been early day logging, however some of the old stumps remain but being badly rotted. I thus found the following evidence for the section corner:

- A badly rotted stump approximately 16 in. dia. in Sec. 29.
- A badly rotted stump approximately 26 in. dia. in Sec. 32.
- A charred stump hole approximately 12 in. dia. in Sec. 31.
- A charred stump hole approximately 12 in. dia. in Sec. 30.

Using Mr. Meldrums bearings and distances from these stumps I then was able to establish a point in which all bearing and distances agreed. At this point I carefully removed the top soil and discovered a change in the color of the soils. A lighter colored soil was in the shape of a 4 in. square, with darker soil around the square. Thus verifying the actual position of the original post Mr. Meldrum set for this section corner.

Description of monument and accessories I established to perpetuate the original location of this corner:

At this section corner I then set a Brass Cap on a 2 in. x 30 in. galvanized iron pipe set within 3 in. of the surface, from which I set four new bearing trees:

- A Lodge Pole Pine 10 in. dia. bears N 30 00 E, 24.95 feet (Horiz. dist.) scribed T 1 S R 40 E S 29 BT.
- A Ponderosa Pine 7 in. dia. bears S 33 30 E, 37.67 feet (Horiz. dist.) scribed T 1 S R 40 E S 32 BT.
- A Ponderosa Pine 7 in. dia. bears S 62 30 W, 41.65 feet (Horiz. dist.) scribed T 1 S R 40 E S 31 BT.
- A Ponderosa Pine 11 in. dia. bears N 66 00 W, 46.65 feet (Horiz. dist.) scribed T 1 S R 40 E S 30 BT.

SEE SURVEY
37-86

UNION COUNTY SURVEYOR
Date Received <u>12-12-86</u>
Date Filed <u>12-22-86</u>
By <u>G. LANGLITZ, DEPUTY</u>
File No. <u>311-86R</u>

REGISTERED PROFESSIONAL LAND SURVEYOR

Thomas H. Hambleton
12-10-86

GREGON JULY 19, 1884 JAMES H. HAMBLETON 645
--

Office of..... County of.....
 State of....., I hereby certify that the within instrument was filed in this office
 for record on the..... day of....., 19.....
 by
 (COUNTY OFFICIAL) (DEPUTY)