


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

No previous History.



Description of corner evidence found:

No evidence found.

Description of monument and accessories established to perpetuate the original location of this corner:

I set a Brass Cap on a 1 in. by 30 in. galvanized iron pipe set within 2 in. of the surface, from which I set two bearing trees:

A Lodge Pole Pine 7 in. dia. bears N 48 22 W, 82.40 feet (Horiz. dist.) and being scribed EC 1/16 S 32 BT.

A Larch 13 in. dia. bears S 55 23 E, 56.87 feet (Horiz. dist.) and being scribed EC 1/16 S 32 BT.

UNION COUNTY SURVEYOR
Date Received <u>12-12-86</u>
Date Filed <u>12-22-86</u>
By <u>G. LANGLITZ, DEPUTY</u>
File No. <u>319-86R</u>

REGISTERED PROFESSIONAL LAND SURVEYOR

James H. Hambleton
12-10-86

OREGON JULY 10, 1964 JAMES H. HAMBLETON 645
--

SEE SURVEY 37-86

Office of..... County of.....
 State of....., I hereby certify that the within instrument was filed in this office
 for record on the..... day of....., 19.....
 by
 (COUNTY OFFICIAL) (DEPUTY)