


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. B-01

History of original corner establishment:

None.



Description of corner evidence found:

No monument found.

BT found:

A 12" Western Larch bears S73½°E, 24.6 ft. (approx. 37½ lks.) blazes healed, origin unknown. Location poster on tree dated 9-21-35.

Description of monument and accessories I established to perpetuate the original location of this corner:

Cap is marked:

T1S
R40E R41E
 | N1/16
 | S6
RLS1848
1986

Corner set by proportioning. I set a 2½"x30" aluminum capped aluminum pipe rising 6" in a mound of stones. Set steel fencepost 3 ft. South.

New BT:

A 7½" Doug. Fir bears N13½°E, 22.9 ft., blazed&scribed: N1/16S6BT

Painted blaze and attached signs as per Standard Specifications for Cadastral Surveys, USFS Region 6, March 1982. A ¾" brass disk stamped "RLS 1848" was nailed to the lower end of the blaze.

Where 6200 begins to climb out of Clark's Creek, a road "Y's" to the right, follow ¼ mile, road turns South. At ¼ mile, go SE uphill 500 ft. to where fenceline from the east intersects the N-S fence, corner is on NW'ly slope.

Compass Declination: 19½°E
Witness: Jeremy Sutton

I hereby certify that the above described corner monument and/or accessories were established as hereon described on Oct. 13, 1986.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

B. A. Sutton

OREGON
JULY 13, 1979
B. A. SUTTON
1848

**UNION COUNTY
SURVEYOR**

Date Received 12-5-86

Date Filed 12-5-86

By G. LANGRISH, DEPUTY

File No. 303-86 R

Office of..... County of.....

State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....

..... by
(COUNTY OFFICIAL) (DEPUTY)