
History of original corner establishment:

Corner originally established by Alonzo Gesner under GLO contract number 683, dated June 7, 1898. Surveyor General record states:

Set basalt stone 12x8x8 ins 8 ins in the ground on top of spur sloping W 300 ft above E fork for 1/4 sec cor marked 1/4 on the W side from which:

A yellow pine 20 in diam bears S34°E 81 lks dist marked 1/4 S3 BT A yellow pine 20 in diam bears N30°30'W 80 lks dist marked 1/4 S4 BT



No record of subsequent monumentation found in Wallowa County survey records.

Description of corner evidence found:

Found stone 12x8x8 inches marked 1/4, set 6 inches in the ground.

Found a 36" diameter P.Pine S34°E 81 lks, live and vigorous with blaze evident. (did not open)

See map of survey dated June, 1987
Description of monument and accessories I established to perpetuate the

original location of this corner: In place of the stone, I set a 2 1/2" x 30" aluminum pipe with aluminum cap marked as shown, 28" in the ground, in mound of stone, 2 ft. base to top of cap, from which:

New BT:

A 17 inch diameter P.Pine bears S44°W, 18.75 feet marked 1/4 S4 BT

Buried the original stone East and alongside of the monument

I hereby certify that the above corner point was perpetuated as hereon described on May 14, 1987.

Witness: Rick Robinson

T1S R41E 70 PLS 644

OREGON
JULY 10, 1961
DUANE 1. GRIFFITH

REGISTERED PROFESSIONAL AND SURVEYOR

I used a steel tape and magnetic compass in the establishment of new accessories. I used 17° East magnetic declination and the distances are to a 50d spike driven in the right side of the root crown. I attached a brass washer marked OPLS 644 to the BT blaze.

Bate Filed 6-10-87
By G, LANGLIEZ DEPUR

☆ GPO--798-276

ANGLIE DEPUTY (SEE SURVEY 16-87)

File No. 22-87 R