


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. J-07

History of original corner establishment:

Original corner established in 1898 by Alonzo Gesner under contract #683. He set a Fir Post 4'x3½"x3½", 24" in ground. From which:
A 6" Black Pine bears N10°E, 23 lks.
A 16" Tamarack bears S13½°E, 33 lks.



Description of corner evidence found:

None.

Description of monument and accessories I established to perpetuate the original location of this corner:

Corner set by proportioning.
I set a 2½"x30" aluminum capped aluminum pipe rising 8" in mound of earth, no stones available. Set a steel fence post 3 ft. north of corner.

Cap is stamped: T1S R41E
S8
¼ S17
RLS1848
1986

New BT's:

A 5" Spruce bears N27¼°W, 22.6 ft., blazed&scribed: ¼S8BT
An 11" Western Larch bears S56°W, 23.8 ft., blazed&scribed: ¼S17BT

Painted blazes and attached signs as required in Specifications for Cadastral Surveys, USFS Region 6, March, 1982. A ¼" brass disk stamped "RLS1848" is nailed to lower end of blazes.

Where 6200510 crests on top of Mt. Moriah flat an old skid road takes off SE'ly follow it for 650 ft., another skid trail goes SW'ly follow it for 350 ft. to edge of tamarack-lodgepole thicket. Corner is S45°W, 350 ft. in thicket.

Compass Declination: 19½°E
Witness: Jeremy Sutton

I hereby certify that the above described corner monument and/or accessories was perpetuated as hereon described on Nov. 7, 1986.



UNION COUNTY SURVEYOR

Date Received 12-3-86
Date Filed 12-5-86
By G. LANGLITZ DEPUTY
File No. 291-86 R

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....

..... by
(COUNTY OFFICIAL) (DEPUTY)