

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


LINE TREE

N2 TO N-3

Line Tree 0.39 chains East of N-03

History of original corner establishment:

Original line tree established in 1898 by Alonzo Gesner under contract #683. At 39.61 chains, a 30" White Fir, a line tree marked with 2 notches on the E. & W. sides.



Description of corner evidence found:

I found a 36" White Fir Stump, No Marks.

Note:

The 36" Fir stump fits well with the 40" Fir stump BT for the 1/4 corner 0.39 chains West and the terrain call to the creek 1.3 chains East as well as the line tree 13.6 chains to the East.

Description of monument and accessories I established to perpetuate the original location of this corner:

I painted a red band and nailed 54-9 signs on the East and West sides.

New BT's:

- A 10 1/2" Spruce bears N47 1/2°E, 35.2 ft., blazed&scribed: APS18BT
- A 4 1/2" Western Larch bears S68°E, 60.4 ft., blazed&scribed: APS19BT

Painted blazes and attached signs as per Standard Specifications for Cadastral Surveys, USFS Region 6, March 1982. A 1/4" brass disk stamped "RLS 1848" was nailed to the lower end of the blazes.

To find corner, from 6200485 follow 6200486 south 500 feet, line tree is west, 100 feet west of the creek on gentle northerly slope.

Compass declination: 19 1/2°E

Witness: Jeremy Sutton

I hereby certify that the above described corner monument and/or accessories were established as hereon described on Nov. 1, 1986.



UNION COUNTY SURVEYOR	
Date Received	<u>12-18-86</u>
Date Filed	<u>12-24-86</u>
By	<u>G. LANGRITZ Deputy</u>
File No.	<u>323-86R</u>

Office of..... County of.....
 State of....., I hereby certify that the within instrument was filed in this office
 for record on the..... day of....., 19.....
 by
 (COUNTY OFFICIAL) (DEPUTY)