


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. N-07

History of original corner establishment:
Original corner established in 1898 by Alonzo Gesner under contract #683
For the corner, he marked an 8" black pine.
From which:
A 30" Yellow Pine bears S50°W, 22 lks.
An 8" Black Pine bears N75°E, 27 lks.



Description of corner evidence found:
Found original corner tree, dead and down, blazes & scribing visible:
"¼S20" on South side, "¼S17" on the North.

Bearing trees found:
A 37" P. Pine stump bears N75°E, 27 lks., badly decayed, no marks.
A 13½" dead, leaning L. Pine bears S50°W, 22 lks., blaze partially healed.

Note: It appears that the tree sizes and species in the original notes were reversed.

Description of monument and accessories established to perpetuate the original location of this corner: Cap is stamped:
From evidence, set 2½"x30"aluminum capped aluminum pipe rising 8" in root hole of corner tree. Set steel fence post 3 ft. north of corner.

T1S R41E
 $\frac{1}{4}$ $\frac{S17}{S20}$
RLS 1848
1986

New BT's:
An 8½" W. Fir bears N31°E, 15.5 ft., blazed&scribed: ¼S17BT
A 8" W. Fir bears S56°E, 8.8 ft. blazed&scribed: ¼S20BT

Painted blazes and attached signs as per Standard Specifications for Cadastral Surveys, USFS Region 6, March 1982. A brass disk stamped "1848" was nailed to the lower ends of the blazes.

On south side of 6200, 350 ft. East of 6200470 there is a hunting camp viewpoint overlooking the Minam. Follow top of Minam breaks 300 ft. NE'ly. to corner

Compass Declination: 19½°E
Witness: Jeremy Sutton
I hereby certify that the above described corner monument and/or accessories were established as hereon described on July 12, 1986.



UNION COUNTY SURVEYOR
Date Received 11-21-86
Date Filed 11-26-86
By G. LANGRISH, DEPUTY
File No. 275-86 R

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....
..... by
(COUNTY OFFICIAL) (DEPUTY)