


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. P-05

History of original corner establishment:

Original corner established in 1898 by Alonzo Gesner under contract #683
He set a stone 18"x15"x8", 12" in ground
From which:
A 7" Tamarack bears S5½°E, 44 lks.
A 10" Black Pine bears N75½°W, 75 lks.



Description of corner evidence found:

Found Stone of the recorded dimensions with a "4" on the west face.

Original bearing trees found:

A 15" W. Larch bears S5½°E, 29.0 ft., blaze healed.
A 13" Lodgepole Pine stump, broken off, dead & down in NW quadrant with blaze and scribing visible: ¼S19BT visible.

Description of monument and accessories I established to perpetuate the original location of this corner:

From original evidence:
Set a 2½"X30" aluminum capped aluminum pipe rising 7" in mound of stones.

Cap is stamped:

T1SR41E

¼
S19|S20

RLS1848
1986

New BT:

A 7½" Fir bears S84°W, 36.2 ft., blazed and scribed: ¼S19BT.
Set steel fence post 3 ft. north of corner.

Painted blazes and attached signs as required in Specifications for Cadastral Surveys, USFS Region 6, March, 1982. A ¼" brass disk stamped "LS1848" nailed to lower end of blazes.
To find corner go SE from the intersection of USFS Rds. 6200 & 6200468 150 ft. to the corner on the west side of large open rock slab clearing.

Compass Declination: 19½°E
Witness: Jeremy Sutton

I hereby certify that the above described corner monument and/or accessories was perpetuated as hereon described on July 12, 1986.



UNION COUNTY SURVEYOR

Date Received 11-21-86
Date Filed 11-26-86
By G. LANGRISH, DEPUTY
File No. 276-86 R

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....
..... by

(COUNTY OFFICIAL)

(DEPUTY)