


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. R-03

History of original corner establishment:
Original corner established in 1898 by A. Gesner under contract #683.
He set a lime stone 16"x14"x8", 12" in ground.
From which:
A 10" Black Pine bears N28°W, 10 lks.
A 7" Tamarack bears S41°W, 18 lks.



Description of corner evidence found:

Found 16"x14"x8" stone with "1/4" on North face, firmly in place.

Bearing trees found:

Found root crown & decayed remains in SW quadrant at record bearing and distance.
Found 12" broken off L Pine bearing N28°W, 10 lks., with blaze&scribing visible: 1/4 19 BT

Description of monument and accessories established to perpetuate the original location of this corner:

Cap is stamped:
From evidence, set 2 1/2"x30" aluminum capped aluminum pipe rising 6" above ground. No stones available.
Deposited original stone along north side in hole.
Set steel fence post 3 ft. north of corner.

T1S R41E

$\frac{1}{4} \frac{S19}{S30}$
RLS 1848
1986

New BT's:

A 10 1/2" W. Fir bears N70 1/2°W, 43.6 ft., blazed&scribed: 1/4 S19BT
A 10" Spruce bears S26 1/2°E, 25.2 ft., blazed&scribed: 1/4 S30BT

Painted blazes and attached signs as required in Specifications for Cadastral Surveys, USFS Region 6, March, 1982. A 3/4" brass disk stamped "LS1848" nailed to lower end of blazes.
From 6200 take 6200437 NW'ly 1/2 mile, as rd. begins to descend down draw, corner is 150' West on North crest of ridge.

Compass Declination: 19 1/2°E
Witness: Jeremy Sutton

I hereby certify that the above described corner monument and/or accessories was perpetuated as hereon described on Aug 23, 1986.



UNION COUNTY SURVEYOR
Date Received 11-21-86
Date Filed 11-26-86
By G. LANGLITZ, DEPUTY
File No. 278-86 R

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....
..... by
(COUNTY OFFICIAL) (DEPUTY)