


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

SURVEYED BY: A. GENSNER, 1898, CONTRACT NO. 683

40.00 SET BASALT STONE 16X4X10 IN 12INS. IN THE GROUND ON STEEP HILL SIDE SLOPING EAST FOR 1/4 SEC COR. MARKED 1/4 ON THE W. SIDE, FROM WHICH:

- A FIR, 12 INS. DIAM., BEARS S.54°E., 18 LKS. DIST. MKD. 1/4 S29 BT
- A FIR, 8 INS. DIAM., BEARS S.37°W., 14 LKS. DIST. MKD. 1/4 S30 BT



Description of corner evidence found:

A FIR, 17" IN DIAM. BEARS S.41°01'W., 9.76', WITH CLOSED BLAZE.

Description of monument and accessories I established to perpetuate the original location of this corner: *

REGISTERED
PROFESSIONAL
LAND SURVEYOR

M A Stoll 9/98

OREGON
JULY 16, 1983
RONALD E. STOLL
2058

SET A 3 1/4" ALUMINUM CAPPED MONUMENT 20" IN THE GROUND, WITH MOUND OF STONE TO CAP, CAP MARKED PER DIAGRAM, FROM WHICH:

- A FIR, 25" IN DIAM. BEARS S.88°10'W., 19.90', SCRIBED "1/4X BT".
- A FIR, 11" IN DIAM. BEARS N.11°11'W., 43.62', SCRIBED "1/4S30 BT".
- A FIR, 7" IN DIAM. BEARS N.87°25'E., 45.82', SCRIBED "1/4S29 BT".

REFERENCE: RECORD OF SURVEY, SKIDDER/EAGLE CAP WILDERNESS SURVEY
WITNESS TO MONUMENT: DAVID SUTHERLAND
BEARINGS TAKEN TO BRASS TAG AT CENTER OF BLAZE, DISTANCES MEASURED TO BRASS TAG ON SIDE CENTER OF TREE. OBSERVED WITH ELECTRONIC TOTAL STATION AND STEEL TAPE.
BASIS OF BEARINGS WAS A SOLAR OBSERVATION.

Office of _____ County of _____
State of _____ I hereby certify that the within instrument was filed in this office
for record on the ____ day of _____, 19____
_____ by _____
(COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY
CLERK

Date Received 10/28/98
File Filed 3/3/99
R. ROBINSON, DEPUTY
File No. 007-1999R