## CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. V-05

DIAGRAM

History of original corner establishment:

Original corner established in 1898 by A. Gesner under contract #683.

He set a pine post 4'x4"x4", 24" in ground. From which:

A 14" Black Pine bears N68°E, 86 lks.

An 14" Black Pine bears S74°E, 59 lks.

An 8" Fir bears S24°W, 120 lks.

A 9" Spruce bears N874°W, 239 1ks.

T1S R41E S30|S29 S31 | S32

Description of corner evidence found:

No corner monument found.

Bearing trees found:

A Spruce stump bears N87%°W, 157.9 ft., no marks visible. A dead and down pine, stump in place, bears N68°E, 56.8 ft., scribing visible: T1SR41Es29BT.

A dead and down tree, badly dacayed, bears S74°E, 38.8 ft.

Description of monument and accessories I established to perpetuate the original location of this corner:

T1S R41E Cap is stamped: From evidence, set 2½"x30" aluminum capped S30 | S29 aluminum pipe rising 10" above ground. S31|S32 No stones available for mound. RLS 1848 Set steel fence post 3 ft. north of corner. 1986

New BT's:

A 6½" W. Fir bears N55½°W, 18.4 ft., blazed&scribed: T1SR41ES30BT A 3" W. Fir bears N69½°E, 32.0 ft., blazed & scribed: "X"BT

A 7½" Spruce bears S74½°E, 60.8 ft., blazed & scribed: T1SR41ES32BT A 7½" Spruce bears S41½°W, 53.2 ft., blazed & scribed T1SR41ES31BT

Painted blazes and attached signs as required in Specifications for Cadastral Surveys, USFS Region 6, March, 1982. A 3" brass disk stamped "LS1848" nailed to lower end of blazes. From 6200 follow 6200433 easterly nile to end of road, corner is S70°E, 450' in marshy area.

Compass Declination: 19₺°E Witness: Jeremy Sutton

I hereby certify that the above described corner monument and/or accessories was perpetuated as hereon described on July 12, 1986.

REGISTERED **PROFESSIONAL** LAND SURVEYOR

> OREGON JULY 13, 1979
> B. A. SUTTON 1848

UNION	COUNTY	
SURVEYOR		

Date Received 11.21.86

Date Filed 11. 26-86

DERM

FIL No. 280-86 R

Office of	1848	<u> </u>
State of, I herei		
for record on the day of		
	by	
(COUNTY OFFICIAL)	(DEPUT	

## CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

SURVEYED BY: A. GENSNER, 1898, CONTRACT NO. 683

80.00 SET PINE POST 4 FEET LONG, 4 IN. SQ, 2 FT IN THE GROUND FOR COR TO SECS. 29, 30, 31 AND 32 MARKED T1S S29 ON THE N-E R41E S32 ON THE S-E S31 ON THE S-W AND S30 ON THE N-W FACES WITH 1 NOTCH ON THE SOUTH AND 5 NOTCHES ON THE EAST EDGES, FROM WHICH:

DIAGRAM
T | S R 4| E
S 30 | S 29
S 31 | S 32
RLS 1848
1986

R. ROBINSON, DEDUTY

A BLACK PINE, 14 INS. DIAM., BEARS N.68°E., 86 LKS. DIST. MKD. T1SR41ES27BT

A BLACK PINE, 14 INS. DIAM., BEARS S.74°E., 59 LKS. DIST. MKD. T1SR41ES32BT A FIR, 8 INS. DIAM., BEARS S.24°W., 120 LKS. DIST. MKD. T1SR41ES31BT A SPRUCE, 9 INS. DIAM., BEARS N.87¼°W., 237 LKS. DIST. MKD. T1SR41ES30BT

Description of corner evidence found:

SURVEYED BY: RLS 1848, 1986.

FOUND A 3" DIAM. ALUMINUM CAPPED PIPE IN A SMALL MOUND OF STONE, CAP MARKED PER DIAGRAM, FROM WHICH:

G-L-O ACCESSORY:

A ROTTED STUMP, BEARS N.64°06'E., 57.11'

RLS 1848 ACCESSORIES:

A FIR (DEAD), 4" IN DIAM. BEARS N.65°50'E., 31.92'.
A FIR, 8" IN DIAM. BEARS S.76°59'E., 60.79', SCRIBED "T1SR41ES32 BT".
A FIR, 7" IN DIAM. BEARS S.28°11'W., 53.18', SCRIBED "T1SR41ES31 BT".
A FIR, 7" IN DIAM. BEARS N.57°25'W., 18.18', SCRIBED "T1SR41ES30 BT".

Description of monument and accessories I established to perpetuate the original location of this corner:

A FIR, 6" IN DIAM. BEARS N.68°25'E., 34.53', SCRIBED "T1SR41ES29 BT".

WITNESS TO MONUMENT BEARINGS TAKEN TO TH TO THE SIDE CENTER OF	E CENTER OF BLAZE, DISTANCES TREE. OBSERVED WITH ELECTR	S MEASURED		
STATION AND STEEL TAP		REGISTERED		
BASIS OF BEARINGS WA	S A SOLAR OBSERVATION.	PROFESSIONAL		
·		LAND SURVEYOR		
		M 4 Stato 9/98		
		OREGON JULY 15, 1983		
		RONALD E. STOLL		
		2058		
Office of	County of	to the same that		
State of I hereby certify that the within instrument was filed in this office				
for record on the da	ay of, 19	to the property of the state of		
(COUNTY OFF	ICIAL) by (DEPUTY)	10/28/98		
)		1-1-0		