


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

R-11

History of original corner establishment:



CORNER IS A 10" TAMARACK MARKED  $\frac{1}{4}$ S ON NORTH FACE

10" FIR S10W 12LKS. MKD.  $\frac{1}{4}$ S BT  
20" TAMARACK N05W 28LKS. MKD.  $\frac{1}{4}$ S.BT

Description of corner evidence found:

RED PAINTED STAKE

12" FIR SNAG S10W 7.9' "BT" PARTIALLY VISIBLE  
24" ROTTEN STUMP N05W 18.5'

Description of monument and accessories I established to perpetuate the original location of this corner:

SET 2"x30" IRON PIPE WITH BRASS-CAP MARKED: T2N R38E  
 $\frac{1}{4}$  S21  
 $\frac{1}{4}$  S28  
1978  
RLS 346

14" FIR N42E 35.0' MKD.  $\frac{1}{4}$  S21 BT  
12" FIR S38W 36.0' MKD.  $\frac{1}{4}$  S28 BT

ALL BT'S HAVE A RED PAINTED STRIPE AND BEARING TREE TAGS. THE NEW BT'S HAVE A BRASS WASHER STAMPED RLS 346 NAILED TO THE LOWER BLAZE. THERE IS A 6' STEEL FENCE POST WITHIN 5' OF THE CORNER.

THERE IS A BLAZED LINE RUNNING WEST THROUGH THIS CORNER.

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*W.D. Harris*

OREGON  
MAY 6, 1955  
WAYNE C. HARRIS  
346

Office of.....COUNTY SURVEYOR..... County of.....UNION.....  
State of.....OREGON..... I hereby certify that the within instrument was filed in this office  
for record on the..... day of....., 19.....  
..... by .....  
(COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY  
SURVEYOR

Date Received \_\_\_\_\_  
Date Filed \_\_\_\_\_  
By \_\_\_\_\_  
File No. 223-83R