

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


History of original corner establishment:

Contract established in 1883 by Frank W. Campbell under Contract No. 468.

80.00 chains set a basalt stone 13" x 10" x 7" 9 inches in the ground with 2 notches on South and East faces.

From which:

- A fir 12" in diam. bears N 62° E 31 lks. marked T 2N R 38E S 22 BT.
- A fir 10" in diam. bears S 51° E 33 lks. marked T 2N R 38E S 27 BT.
- A fir 24" in diam. bears S 4° W 12 lks. marked T 2N R 38E S 28 BT.
- A fir 12" in diam. bears N 18° W 21 lks. marked T 2N R 38E S 21 BT.



Description of corner evidence found:

Found the stone as described.

Found the BT SW, now 38" in diam.



James H. Buisman

OREGON
JULY 22, 1977
JAMES H. BUISMAN
1097

Description of monument and accessories established to perpetuate the original location of this corner

At the position described above, I set a 2½" x 30" aluminum pipe 10" in the ground with an aluminum cap marked as shown. Raised stone mound around cap.

From which I scribed BTs:

- A fir 12" in diam. bears N 0°29' E 22.1' marked T 2N R 38E S 22 BT.
- A fir 9" in diam. bears S 74°08' E 4.9' marked T 2N R 38E S 27 BT.
- A fir 8" in diam. bears N 75°13' W 20.5' marked T 2N R 38E S 21 BT.

I nailed a brass washer marked OPLS 1097 to BT blazes.


I set a steel fence post N 45° W 1.7' with signs 54-4 and 54-9.

I painted a red band around BTs and face of scribe.

I used a steel tape and Wild T-2 and measured a horizontal distance to the center of the BTs.

This corner was set September 30, 1980. Witness by Patrick L. Murphy.

See map of survey.



Office of..... County of.....
 State of....., I hereby certify that the within instrument was filed in this office
 for record on the day of.....
 by
 (COUNTY OFFICIAL) (DEPUTY)

**UNION COUNTY
SURVEYOR**

Date Received _____

Date Filed _____

By _____

File No. 224-83R

GPO 796-333