CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1883 by Frank W. Campbell under Contract No. 468.

80.00 chains. Set fir post $4\frac{1}{2}$ long, 4" square, with marked stone 24" in the ground marked T 2N , S 27 on Northeast face, R 38E S 34 on Southeast face, S 28 on Northwest face, and S 33 on Southwest face with 1 notch on South edge and 3 $\,$ notches on East edge. From which:

V-13 DIAGRAM TZN R3BE 28/27

A fir 18" in diam. bears N 30° E 48 lks. marked T 2N R 38E S 27 BT. A fir 10" in diam. bears S 23° E 11 lks. marked T 2N R 38E S 34 BT. A fir 10" in diam. bears S 23° W 11 lks. marked T 2N R 38E S 33 BT. A fir 20" in diam. bears N 16° W 24 lks. marked T 2N R 38E S 28 BT.

Description of corner evidence found:

None found.

REGISTERED **PROFESSIONAL** LAND SURVEYOR ame H Busmin OREGON JULY 22, 1977 JAMES H. BUISMAN

Description of monument and accessories I established to perpetuate the original location of this corner

At the position described above, I set a $2\frac{1}{2}$ " x 30" aluminum pipe 26" in the ground with an aluminum cap marked as shown.

From which I scribed BTs:

N 72º11' E Fir 8"

5 50° 25' E Fir 6"

5 71° 50" W Fir 6"

N 27 34 W Fir 10"

28.2 Ft. marked TIN R38E 527BT

9.8 Ft. marked T2N R38E 534 BT

29.9 Fl. marked TINRZBE & 33BT

9.3 F1 marked T2N R3BE S 28 BT

I nailed a brass washer marked OPLS 1097 to BT blazes.

I set a steel fence post 5' North with Signs 54-4 & 54-2 & 5' East with Sign 54-2

I painted a red band around BTs and face of scribe.

I used a steel tape and T-2 Throdolike to measure to the Center of BT

This corner was set October 16,1980, Witness by Patrick L. Murphy

Witness by David H. Krumbeln

See map of survey.

..... County of

State of......, I hereby certify that the within Instrument was filed in this office

for record on the day of

(DEPUTY)

UNION COUNTY SURVEYOR Date Received File No. 240 - 83R

Form R6-7100-57 (9/71)