CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1883 by Frank W. Campbell under Contract No. 468.

80.00 chains. Set a post $4\frac{1}{2}$! long, 4" square, with marked stone 24" in ground marked T 2N S 26 on Northeast face, R 38E S 35 on Southeast face, S 34 on Southwest face and S 27 on Northwest faces with 1 notch on South face and 2 notches on East edges. From which:

V-17
DIAGRAM
72H R38E
27 26 34 35

											marked							
Α	fir	10"	in	diam.	bears	S	650	Ε	19	lks.	marked	T	2N	R	38E	S	35	BT.
Α	fir	10"	in	diam	hears	ς	720	W	55	1ks.	marked	Т	2N	R	38F	S	34	RT.

A fir 14" in diam. bears N 14° W 12 lks. marked T 2N R 38E S 27 BT.

Description of corner evidence found:

None found.

REGISTERED **PROFESSIONAL** LAND SURVEYOR Juisman remio H OREGON JULY 22, 1977 JAMES H. BUISMAN 1097

TZH E38E

27/26

34/35

1980

1097

Description of monument and accessories I established to perpetuate the original location of this corner

At the position described above, I set a $2\frac{1}{2}$ " x 30" aluminum pipe 21" in the ground with an aluminum cap marked as shown.

From which I scribed BTs:

A fir 8" in diam. bears N 68°36' E 57.6' marked T 2N R 38E S 26

A fir 9" in diam. bears S $07^{\circ}32$ ' E 42.0' marked T 2N R 38E S 35 BT. A fir 9" in diam. bears S $44^{\circ}12$ ' W 95.9' marked T 2N R 38E S 34 BT. A fir 15" in diam. bears N $86^{\circ}29$ ' W 28.4' marked T 2N R 38E S 27 BT.

I nailed a brass washer marked OPLS 1097 to BT blazes.

I set a steel fence post 1' East with signs 54-4 and 54-9.

I painted a red band around BTs and face of scribe.

I used a steel tape and Wild T-2 and measured a horizontal distance to the center of the BTs.

This corner was set October 1, 1980. Witness by Patrick L. Murphy.

See map of survey.

Office of	County of	
	, I hereby certify that the within instrument was filed i	
for record on the day	y of	
	by	
(COUNTY OFFI		

UNION COUNTY SURVEYOR Date Received Date Filed File No. 243-83P

Form R6-7100-57 (9/71)