


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. E-7

History of original corner establishment:

Corner established by Rufus S. Moore under GLO contract No. 382 in July, 1881. Surveyors General's notes state: Set post for 1/4 sec. cor; from which A tamarac, 36 ins. diam. bears S50°W, 16 lks. dist. A pine 4 ins. diam. bears N45°W, 36 lks. dist."




Description of corner evidence found:

Found no trace of wood post. From a 30" tamarac scribed BT on lower blaze, measured N50°E, 10.5 ft. No trace of pine BT. Boise Cascade location tag on old BT. Magnetic variation used. N20°E.

Description of monument and accessories I established to perpetuate the original location of this corner:

At the above described point set 2 1/2" x 30" galvanized pipe with brass cap marked: Set pipe 25" in the ground. No rock in the area. From which: A 10" tamarac bears N07°E, 66.8 ft. scribed 1/4 S5 BT. Painted blazes red and 6" red band around. Placed 54-3 and brass washer stamped PLS 1051 on BT.



I hereby certify that the above corner monument was reestablished as herein described.

Witnesses: David L. Landers
Daniel T. Rowland
Ray McVey

May 31, 1979

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

Barry B. Barbour

**OREGON
OCT. 17, 1979
BARRY B. BARBOUR
1051**

Office of..... County Surveyor..... County of..... Union.....
State of Oregon....., I hereby certify that the within instrument was filed in this office
for record on the 19th day of..... June....., 19..79
..... by

(COUNTY OFFICIAL)

(DEPUTY)

**UNION COUNTY
SURVEYOR**

Date Received _____

Date Filed _____

By _____

File No. 267-83R

GPO 799-509

HORIZONTAL CONTROL DATA

UNION COUNTY, OREGON

OREGON STATE PLANE, NORTH ZONE (3601)

STA NAME: 200505

1/4 SECTION CORNER COMMON TO SECTIONS: 5 and 8

TWP. 2 N. RGE. 39 E.

GEODETIC COORD: NAD 83(91)

DATE TIED: July 5, 2005

LAT: 45 ° 40 ' 29.40698 " N

SURVEYOR: RICK G. ROBINSON
OPLS 2219

LONG: 117 ° 57 ' 48.06895 " W

FIRM: BAGETT, GRIFFITH, & BLACKMAN
2006 ADAMS AVENUE
LAGRANDE, OR 97850
(541) 963-6092

SP. COOR: NAD 83(91)

N: 742312.671 INT FT.

E: 8850391.511 INT FT.

TYPE: GPS

THETA: 1 ° 48 ' 2.12620735 "

ORDER: SECOND CLASS: 1


SCALE FACTOR: 0.9999336078

ELEV: 3624.14 US FT.

ELEV: DATUM: NGVD 29

COMMENTS:

Corner is 2 1/2" Brass Cap on a 2 1/2" iron pipe marked as shown:



REGISTERED
PROFESSIONAL
LAND SURVEYOR

Rick G. Robinson
OREGON
July 17, 1988
RICK G. ROBINSON
2219

Renewal Date: December 31, 2006

1 METER = 3.280833333... US FEET = 39.37 INCHES

1 METER = 3.280839895 INT'L FEET OR 1 INCH = 2.54 CM

TO CALCULATE ELEVATION FACTOR (IN THE NORTH AMERICAN CONTINENT)

DIVIDE 20,906,000 BY (20,906,000 + ELLIPSOID ELEV. IN FEET)