


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. E-9

History of original corner establishment:

Corner established by Rufus S. Moore under GLO contract No. 382 in July, 1881. Surveyors General's notes state: "Set post for cor. to secs. 4, 5, 8, and 9; from which A tamarac 18 ins. diam., bears N28°E, 32 lks. dist. A tamarac 20 ins. diam., bears N37°W, 24 lks. dist. A tamarac 20 ins. diam., bears S68°W, 32 lks. dist. A fir 7 ins. diam., bears S33°E, 49 lks. dist."




Description of corner evidence found:

Found no trace of wood post. Found tamarac dead and down with scribed BT. From stump hole measured S37°E, 15.8 ft. Rotton stump bears S32°E, 32.4 ft.(slope) and 31.7 ft.(horz). Magnetic variation used. N20°E.

Description of monument and accessories established to perpetuate the original location of this corner:

At above described point set 2 1/2" x 30" galvanized pipe with brass cap marked:
Set pipe 24" in the ground and mound of stone around to cap.



From which: A 14" fir bears N59°E, 21.5 ft. scribed T2NR39E S4 BT. A 14" tamarac bears S18°E, 91.3 ft. scribed T2NR39E S9 BT. A 10" tamarac bears S42°W, 36.6 ft. scribed T2NR39E S8 BT. An 11" fir bears N45°W, 30.4 ft. scribed T2NR39E S5 BT. Painted blazes red and 6" red band around. Placed 54-3 and brass washer stamped PLS 1051 on BTs.

I hereby certify that the above corner monument was reestablished as herein described.

Witnesses: David L. Landers
Daniel T. Rowland
Ray McVey

May 31, 1979

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

Barry B. Barbour

**OREGON
OCT. 17, 1978
BARRY B. BARBOUR
1051**

Office of.....County Surveyor..... County of..... Union.....

State of Oregon.....

I hereby certify that the within instrument was filed in this office for record on the 19th day of June, 1979.

..... by
(COUNTY OFFICIAL)

(DEPUTY)

Form R6-7100-57 (9/71)

LAND SURVEYOR

Date Received _____

Date Filed _____

By _____

GPO 799-509

File No. 268-83R

HORIZONTAL CONTROL DATA

UNION COUNTY, OREGON

OREGON STATE PLANE, NORTH ZONE (3601)

STA NAME: 200506

SECTION CORNER COMMON TO SECTIONS: 4, 5, 8 and 9

TWP. 2 N. RGE. 39 E.

GEODETIC COORD: NAD 83(91)

DATE TIED: June 1, 2005

LAT: 45 ° 40 ' 29.59373 " N

SURVEYOR: RICK G. ROBINSON
OPLS 2219

LONG: 117 ° 57 ' 10.57674 " W

FIRM: BAGETT, GRIFFITH, & BLACKMAN
2006 ADAMS AVENUE
LAGRANDE, OR 97850
(541) 963-6092

SP. COOR: NAD 83(91)

N: 742415.317 INT FT.

E: 8853051.673 INT FT.

TYPE: GPS

THETA: 1 ° 48 ' 22.8267589 "

ORDER: SECOND CLASS: 1


SCALE FACTOR: 0.9999335883

ELEV: 3470.98 US FT.

ELEV: DATUM: NGVD 29

COMMENTS:

Corner is 2 1/2" Brass Cap on a 2 1/2" iron pipe marked as shown:



REGISTERED
PROFESSIONAL
LAND SURVEYOR

Rick G. Robinson
OREGON
July 17, 1986
RICK G. ROBINSON
2219

Renewal Date: December 31, 2006

1 METER = 3.2808333333... US FEET = 39.37 INCHES

1 METER = 3.280839895 INT'L FEET OR 1 INCH = 2.54 CM

TO CALCULATE ELEVATION FACTOR (IN THE NORTH AMERICAN CONTINENT)

DIVIDE 20,906,000 BY (20,906,000 + ELLIPSOID ELEV. IN FEET)