UNION COUNTY SURVEYOR CERTIFIED RECORD OF LAND CORNER MONUMENTATION

HISTORY OF ORIGINAL CORNER ESTABLISHMENT:

Corner not previously established.

No record of monumentation found in UNION COUNTY survey records.

DESCRIPTION OF CORNER EVIDENCE FOUND:

Corner not previously established.

See Survey Number 015-2005.

DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

At the position determined by said survey, I set a 5/8" x 30" iron pin with 1 ½" aluminum cap marked as shown below, 34" in the ground, in North edge of existing forest road, from which:

NEW BEARING TREES:

A 6 inch diameter Ponderosa Pine bears S $13^{\circ}W$, a distance of 54.00 feet, marked E1/16 S17 BT.

A 14 inch diameter Tamarack bears N $38\,^{\circ}\text{W}$, a distance of 48.80 feet, marked E1/16 S8 BT.

I hereby certify that the corner was monumented on July 6, 2005. Witness: Greg Blackman Jr. and Rick Thew

REGISTERED PROFESSIONAL LAND SURVEYOR

OREGON
July 17, 1986
RICK G. ROBINSON

Renewal Date: December 31, 2006

2219

T2N R39E

S 8

S 17

2005

OPLS 2219

T2N R39EJ-08

8

S

UNION COUNTY
SURVEYOR

Date Received 7/28/65

Date Filed By 4 7 6 6 5

Filed By 4 7 6 6 7

File Number 609-2005 R

I used a steel tape and magnetic compass in the establishment of new accessories. The magnetic declination used was 17° East. The distance to the bearing trees is to a 50d spike driven on the right side of the tree at the root crown. I attached a brass washer marked OPLS 2219 to the BT blaze.