
## CERTIFIED RECORD OF LAND CORNER MONUMENTATION

### HISTORY OF ORIGINAL CORNER ESTABLISHED:

Corner not previously established

# T2N R39EP-14



DESCRIPTION OF CORNER EVIDENCE FOUND:

None.

SEE SURVEY NUMBER 024-2017

### DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED

#### TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

At position determined by survey, I set a 5/8" x 30" iron pin, 25" in the ground, with a 2 ½" Aluminum cap marked as shown below, from which:

### NEW BEARING TREES:

A 6" Ponderosa Pine bears South 32° West, a distance of 11.80 feet, marked CW 1/16 S22 BT. A 9" Ponderosa Pine bears North 65° West, a distance of 7.75 feet, marked CW 1/16 S22 BT.

Set a steel fencepost North approx. 1 ft.

I hereby certify that the corner was monumented June 14, 2017.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREON
June 2, 2010
JEFFREY S. HSU
83571

Renewal Date: June 30, 2019

C S22

2017
OPLS 83571

UNION COUNTY SURVEYOR

Date Received

Date File

Filed By

File Number 010-2017/

I used a steel tape and magnetic compass in the establishment of the bearing trees. Magnetic declination used was 13° East. Bearings are to a brass washer marked OPLS 83571 in the lower blaze of the tree. Distance is to a spike set in the root crown of the side of the tree.