


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

HISTORY OF ORIGINAL CORNER ESTABLISHED:

Corner not previously established

T 2 N R 39 E Q-15



DESCRIPTION OF CORNER EVIDENCE FOUND:

None.

SEE SURVEY NUMBER 024-2017

DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED

TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

At position determined by survey, I set a 5/8" x 30" iron pin, 25" in the ground, with a 2 1/2" Aluminum cap marked as shown below, from which:

NEW BEARING TREES:

A 15" Ponderosa Pine bears North 86° East, a distance of 48.30 feet, marked CS 1/16 S22 BT.
A 12" Ponderosa Pine bears South 3° East, a distance of 28.15 feet, marked CS 1/16 S22 BT.

Set a steel fencepost North approx. 0.5 ft.

I hereby certify that the corner was monumented June 12, 2017.


Witness: Kyle Tucker

REGISTERED
PROFESSIONAL
LAND SURVEYOR



OREGON
June 2, 2010
JEFFREY S. HSU
83571

Renewal Date: June 30, 2019



**UNION COUNTY
SURVEYOR**

Date Received 6/22/17

Date Filed 6/22/17

Filed By MLG

File Number 018-2017R

I used a steel tape and magnetic compass in the establishment of the bearing trees. Magnetic declination used was 13° East. Bearings are to a brass washer marked OPLS 83571 in the lower blaze of the tree. Distance is to a spike set in the root crown of the side of the tree.