


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

R-17

History of original corner establishment:

A basalt stone 16" x 12" x 8" in a mound of stone is what was set for the section corner to Sec's 22, 23, 26, and 27.



Description of corner evidence found:

Found a stone 16" x 12" x 8" with 2 notches on east edges and 2 notches on south edges in the center of a mound of stone as described in the GLO notes.

Description of monument and accessories established to perpetuate the original location of this corner

I set a 5/8" x 30" iron pin with a cap stamped RLS 645 alongside the marked stone in the mound of stone, leaving the stone in its original position. Since there were no original bearing trees set, I then set four new bearing trees as follows:

A pine 7" dia. which bears N 47 E, 69.1 feet scribed T 2 N R 39 E S 23 BT.

A pine 7" dia. which bears S 26 E, 89.9 feet scribed T 2 N R 39 E S 26 BT.

A pine 9" dia. which bears S 75 W, 125.3 feet scribed T 2 N R 39 E S 27 BT.

A pine 19" dia. which bears N 37 W, 77.1 feet scribed T 2 N R 39 E S 22 BT.

Note: Since the corner is on a hillside all distances to bearing trees have been reduced to horizontal distances.

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office
for record on the day of.....
..... by.....
(COUNTY OFFICIAL) (DEPUTY)

REGISTERED
PROFESSIONAL
LAND SURVEYOR

James H. Hambleton
12-20-77

OREGON
JULY 10, 1964
JAMES H. HAMBLETON
645

UNION COUNTY SURVEYOR

Date Received _____

Date Filed _____ ☆ GPO 796-333

By _____

File No. 287-83R