

**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

**HISTORY OF ORIGINAL CORNER ESTABLISHED:**


Original corner set by Rufus S. Moore, under GLO contract No. 382, dated March 23, 1881. Surveyor General Record States:

Set Basalt Stone 16 x 12 x 8 in mound of stone for 1/4 sec. cor.

A House bears S27°W, 15 chs. dist.

In Survey Number 108-77, James H. Hambleton, found a 16 x 12 x 8 stone in mound of stone and set a 5/8" iron pin alongside.

T 2 N R 39 E R-19



**DESCRIPTION OF CORNER EVIDENCE FOUND:**

Found a 5/8" iron pin 17" above ground in corner of steel "I" beam rock jack from which fences bear East, West, and North.

**DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED**

**TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:**

From iron pin:

**NEW BEARING OBJECTS:**

- A 7" Ponderosa Pine bears North 17° East, a distance of 28.55 feet, marked 1/4S23 BT.
- A stone outcrop, the exposed face measuring 5' x 4' x 3' above ground bears South 65° East, a distance of 33.95 feet, marked X on top and BO on South West face.
- A 12" Douglas Fir bears South 46° West, a distance of 17.50 feet, marked 1/4S26 BT.
- A 6" Ponderosa Pine bears North 85° West, a distance of 20.85 feet, marked 1/4S23 BT.

I hereby certify that the corner was perpetuated November 17, 2017.

Witness: Kyle Tucker, Terrell Croghan

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

OREGON  
June 2, 2010  
JEFFREY S. HSU  
83571

Renewal Date: June 30, 2019

**UNION COUNTY  
SURVEYOR**

Date Received 12/14/17

Date Filed 12/14/17

Filed By [Signature]

File Number 058-2017R

I used a steel tape and magnetic compass in the establishment of the bearing trees and objects. Magnetic declination used was 13° East. Bearing is to a brass washer marked OPLS 83571 in the lower blaze of the trees and to the center of X for the outcrop. Distance is to a spike set in the root crown of the side of the trees and center of X for the outcrop.