


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

R-21

History of original corner establishment:



A wooden post was set for the section corner from which the following bearing trees were set:

- A pine 34" dia. bears N 45 E 92 lks.
- A pine 22" dia. bears S 63 W 57 lks.
- A pine 24" dia. bears S 55 E 58 lks.
- A tamarack 5" dia. bears N 50 W, 23 lks.

Description of corner evidence found:

Found evidence of the bearing tree stumps located in sections 24, 25, and 26. Though stumps were badly rotted they fit the GLO call bearings and distances.

Description of monument and accessories established to perpetuate the original location of this corner

Restored section corner to its original position, using the GLO notes, thus I set a 5/8" x 30" iron pin with cap stamped RLS 645, in a mound of stone. I then set four new bearing trees as follows:

- A fir 5" dia. which bears N 70 E, 16.3 feet scribed T 2 N R 39 E S 24 BT.
- A fir 10" dia. bears S 58 E, 24.5 feet, scribed T 2 N R 39 E S 25 BT.
- A fir 11" dia. bears S 41 W, 48.3 feet, scribed T 2 N R 39 E S 26 BT.
- A larch 4" dia. bears N 27 W, 16.3 feet scribed T 2 N R 39 E S 23 BT.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

James H. Hambleton
12-20-77

OREGON
JULY 10, 1964
JAMES H. HAMBLETON
645

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office
for record on the day of

..... by

(COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY SURVEYOR	
Date Received	_____
Date Filed	_____
☆ GPO 796-333	
By	_____
File No.	288-83R