CERTIFIED RECORD OF LAND CORNER MONUMENTATION


HISTORY OF ORIGINAL CORNER ESTABLISHED:

Corner was originally established under GLO contract number No. 437, dated June 3rd, 1882, executed by Rufus Moore. Surveyor General field notes state:

Set post for cor to secs 2 & 3 from which,

A pine 18 ins diam bears N 79° E 71 lks dist A pine 5" diam bears N 14° W 69 lks dist A pine 5 ins diam bears S 53° W 194 lks dist A pine 34 ins diam bears S 30° E 131 lks dist

In survey for Road Petition 580, Arthur Curtis notes a stone at the section corner position.



DESCRIPTION OF CORNER EVIDENCE FOUND:

No remaining evidence of original GLO corner found. Position falls in a North/South running dirt road.

SEE SURVEY NUMBER CS 2025-019(Wallowa Co)/SURVEY NUMBER 022-2025 (Union Co)

DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED TO MONUMENT THE

ORIGINAL LOCATION OF THIS CORNER:

At proportionate position, I set a $5/8" \times 30"$ iron pine with a 2 1/2" aluminum cap, marked as shown below, 30" in the ground, from which:

NEW BEARING OBJECTS:

An 11" Ponderosa Pine bears North 65° East, a distance of 16.20 feet, marked T3N R40E S35 BT

A 14" Ponderosa Pine bears South 27° East, a distance of 94.00 feet, marked T2N R40E S2 BT

A 12" Ponderosa Pine bears South 36° West, a distance of 55.00 feet, marked T2N R40E S3 BT $\,$

A 10" Ponderosa Pine bears North 10° West, a distance of 110.70 feet, marked T3N R40E S34 BT $\,$

I hereby certify that the corner was monumented on June 18th, 2025

Witness: Kyle Tucker, Adam Gordon

REGISTERED

PROFESSIONAL LAND SURVEYOR

S34 S35
S3 S2

2025
OPLS 83571

OREGON June 2, 2010 JEFFREY S. HSU

83571 Renewal Date: June 30, 2027 I used a tape and compass in the establishment of the new bearing trees. 14° East was used for declination. Bearings measures to a brass washer marks OPLS 83571 in the BT blaze. Distance measured to a 60d spike in the side of the tree.

UNION COUNTY
SURVEYOR

Date Received 6/26/25

Date Filed By

File Number 024-2025R