CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:


Original corner set by Rufus S. Moore under contract No. 382 dated March 23, 1881, and approved March 21, 1882. Record States: Set post for 1/4 sec. cor. From Which: A fir, 7 ins. diam., bears N. 33° E., 34 lks. dist. A tamarack, 16 ins. diam., bears S. 70° W., 10 lks. dist.

Subsequent survey:

Corner re-established by James H. Hambleton, LS 645, as shown on CS 003-1970. Record States:

Made extensive search, but was unable to find any evidence, therefore used the old existing fence corner as the 1/4 corner.

Township 2 North, Range 40 East





Description of evidence found:

Found embedded remains of old rock jack in timber at E-W-S fence intersection point, fence now corners on Douglas fir tree.

Description of monument and accessories established to perpetuate the location of this corner.

At position of fence intersection point, I set a 2 ins. diam. aluminum cap, on a 5/8 ins. diam. x 30 ins long iron rod, marked as shown.

From which:

A Douglas fir, 7 ins. diam., bears N. 45° E., 33.0 ft. dist., marked "X BT" on a single blaze.

A Douglas fir, 25 ins. diam., bears S. 65° E., 24.0 ft. dist., marked "1/4 S5 BT" on a single blaze. A ponderosa pine, 5 ins. diam., bears S. 42° W., 7.0 ft. dist., marked "X BT" on a double blaze. A ponderosa pine, 20 ins. diam., bears N. 45° W., 21.1 ft. dist., marked "1/4 S6 BT" on a single blaze.

Corner position falls in timber on mostly level ground from which fences bear E-W-S.

Bearings are made with a hand compass, magnetic declination = 15°E.

I hereby certify that the above corner point was perpetuated as herein described on 5/18/2018.

Witnessed by: Matt Brockamp, LS Austin Brockamp

UNION COUNTY SURVEYOR
Date Received 7 19
Date Filed 9/13/18
Filed By 16 GMuin
File Number 044 - 2018R

